

**Balluff / BIS L-6023-025-050-03-ST13**

RFID bileşeni

**Üretici ürün kodu: BIS00EE**

Seri: BIS



Balluff BIS L-6023-025-050-03-ST13 (BIS00EE), rfid bileşeni. Gövde malzemesi: Aluminium, Die casting; Ürün grubu: LF (125 kHz); Arayüz: DeviceNet galvanically isolated.

**TEKNİK ÖZELLİKLER**

|                                                   |                                       |
|---------------------------------------------------|---------------------------------------|
| <b>Gövde malzemesi</b>                            | Aluminium, Die casting                |
| <b>Ürün grubu</b>                                 | LF (125 kHz)                          |
| <b>Arayüz</b>                                     | DeviceNet galvanically isolated       |
| <b>Supported RFID technologies</b>                | LF 125 kHz (BIS L)                    |
| <b>Number of connectable R/W heads / antennas</b> | 2                                     |
| <b>Çalışma gerilimi Ub</b>                        | 19.2...28.8 VDC                       |
| <b>Ortam sıcaklığı</b>                            | 0...60 °C                             |
| <b>IP koruma derecesi</b>                         | IP65, with connector                  |
| <b>Onay ve uygunluk</b>                           | CE UL-FILE E227256, Vol.X1, BIS       |
| <b>Bağlantı</b>                                   | Male, 5-pin Female, 5-pin Male, 5-pin |

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

Balluff / BIS L-6023-025-050-03-ST13

LF RFID processors (125 kHz)

Part/model code: BIS00EE

Series: BIS



Balluff BIS L-6023-025-050-03-ST13 (BIS00EE): lf rfid processors (125 khz). Housing material: Aluminium, Die casting; Product group: LF (125 kHz); Interface: DeviceNet galvanically isolated.

TECHNICAL HIGHLIGHTS

|                                            |                                       |
|--------------------------------------------|---------------------------------------|
| Housing material                           | Aluminium, Die casting                |
| Product group                              | LF (125 kHz)                          |
| Interface                                  | DeviceNet galvanically isolated       |
| Supported RFID technologies                | LF 125 kHz (BIS L)                    |
| Number of connectable R/W heads / antennas | 2                                     |
| Operating voltage Ub                       | 19.2...28.8 VDC                       |
| Ambient temperature                        | 0...60 °C                             |
| IP rating                                  | IP65, with connector                  |
| Approval/Conformity                        | CE UL-FILE E227256, Vol.X1, BIS       |
| Connection                                 | Male, 5-pin Female, 5-pin Male, 5-pin |

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.