

Balluff / BNS 819-B06-D08-40-55-1078

Mekanik konum anahtarı

Üretici ürün kodu: BNS01ZU

Seri: BNS



Balluff BNS 819-B06-D08-40-55-1078 (BNS01ZU), mekanik konum anahtarı. Bağlantı tipi: 1-6. Switch position: Screw terminal; Gövde malzemesi: Aluminium, Anodized; Boyutlar: 40 x 66 x 60 mm.

TEKNİK ÖZELLİKLER

Bağlantı tipi	1-6. Switch position: Screw terminal
Gövde malzemesi	Aluminium, Anodized
Boyutlar	40 x 66 x 60 mm
Anahtarlama konumu sayısı	6x Chisel
Çalışma prensibi	1-2. Switch position: Mechanical 3-6. Switch position: Inductive
Sürekli akım	1-2. Switch position: 5 A 3-6. Switch position: 0.13 A
Anma çalışma gerilimi Ue	1-2. Switch position: 250 V AC 3-6. Switch position: 24 V DC
Montaj	parallel
Yaklaşma yönü	longitudinal, parallel to attachment surface
Yaklaşma hızı	1-2. Switch position: 20 m/min
Anahtarlama konum aralığı	8 mm
Ortam sıcaklığı	-5...70 °C

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

Balluff / BNS 819-B06-D08-40-55-1078

Multiple-position cam switches with mixed connections

Part/model code: BNS01ZU

Series: BNS



Balluff BNS 819-B06-D08-40-55-1078 (BNS01ZU): multiple-position cam switches with mixed connections. Connection type: 1-6. Switch position: Screw terminal; Housing material: Aluminium, Anodized; Dimension: 40 x 66 x 60 mm.

TECHNICAL HIGHLIGHTS

Connection type	1-6. Switch position: Screw terminal
Housing material	Aluminium, Anodized
Dimension	40 x 66 x 60 mm
Number of switching positions	6x Chisel
Operating principle	1-2. Switch position: Mechanical 3-6. Switch position: Inductive
Continuous current	1-2. Switch position: 5 A 3-6. Switch position: 0.13 A
Rated operating voltage Ue	1-2. Switch position: 250 V AC 3-6. Switch position: 24 V DC
Installation	parallel
Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-2. Switch position: 20 m/min
Switch position spacing	8 mm
Ambient temperature	-5...70 °C

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.