

Balluff / BNS 819-B08-R08-46-13

Mekanik konum anahtarı

Üretici ürün kodu: BNS0215

Seri: BNS



Balluff BNS 819-B08-R08-46-13 (BNS0215), mekanik konum anahtarı. Bağlantı tipi: 1-8. Switch position: Screw terminal; Gövde malzemesi: Aluminium, Anodized; Boyutlar: 72 x 96 x 48 mm.

TEKNİK ÖZELLİKLER

Bağlantı tipi	1-8. Switch position: Screw terminal
Gövde malzemesi	Aluminium, Anodized
Boyutlar	72 x 96 x 48 mm
Anahtarlama konumu sayısı	8x Roller
Sürüm	Snap contact
Çalışma prensibi	1-8. Switch position: Mechanical
Sürekli akım	1-8. Switch position: 0.1 A
Anma çalışma gerilimi Ue	1-8. Switch position: 250 V AC
Montaj	Vertical
Yaklaşma yönü	longitudinal, parallel to attachment surface
Yaklaşma hızı	1-8. Switch position: 60 m/min
Anahtarlama konum aralığı	8 mm

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

Balluff / BNS 819-B08-R08-46-13

Mechanical multiple position limit switches

Part/model code: BNS0215

Series: BNS



Balluff BNS 819-B08-R08-46-13 (BNS0215): mechanical multiple position limit switches. Connection type: 1-8. Switch position: Screw terminal; Housing material: Aluminium, Anodized; Dimension: 72 x 96 x 48 mm.

TECHNICAL HIGHLIGHTS

Connection type	1-8. Switch position: Screw terminal
Housing material	Aluminium, Anodized
Dimension	72 x 96 x 48 mm
Number of switching positions	8x Roller
Version	Snap contact
Operating principle	1-8. Switch position: Mechanical
Continuous current	1-8. Switch position: 0.1 A
Rated operating voltage Ue	1-8. Switch position: 250 V AC
Installation	Vertical
Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-8. Switch position: 60 m/min
Switch position spacing	8 mm

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.