

**Balluff / BNS 813-B02-D12-72-10-01**

Mekanik konum anahtarı

Üretici ürün kodu: BNS0224

Seri: BNS



Balluff BNS 813-B02-D12-72-10-01 (BNS0224), mekanik konum anahtarı. Bağlantı tipi: 1-2. Switch position: Screw terminal; Gövde malzemesi: Aluminium, Anodized; Boyutlar: 84 x 90 x 77 mm.

**TEKNİK ÖZELLİKLER**

|                                  |                                      |
|----------------------------------|--------------------------------------|
| <b>Bağlantı tipi</b>             | 1-2. Switch position: Screw terminal |
| <b>Gövde malzemesi</b>           | Aluminium, Anodized                  |
| <b>Boyutlar</b>                  | 84 x 90 x 77 mm                      |
| <b>Anahtarlama konumu sayısı</b> | 2x Chisel                            |
| <b>Sürüm</b>                     | Safety EN 60204-1                    |
| <b>Çalışma prensibi</b>          | 1-2. Switch position: Mechanical     |
| <b>Sürekli akım</b>              | 1-2. Switch position: 6 A            |
| <b>Anma çalışma gerilimi Ue</b>  | 1-2. Switch position: 250 V AC       |
| <b>Montaj</b>                    | Horizontal                           |
| <b>Yaklaşma yönü</b>             | Vertical to mounting surface         |
| <b>Yaklaşma hızı</b>             | 1-2. Switch position: 40 m/min       |
| <b>Anahtarlama konum aralığı</b> | 12 mm                                |

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

## Balluff / BNS 813-B02-D12-72-10-01

Mechanical multiple position limit switches with safety switch positions

**Part/model code: BNS0224**

Series: BNS



Balluff BNS 813-B02-D12-72-10-01 (BNS0224): mechanical multiple position limit switches with safety switch positions. Connection type: 1-2. Switch position: Screw terminal; Housing material: Aluminium, Anodized; Dimension: 84 x 90 x 77 mm.

### TECHNICAL HIGHLIGHTS

|                               |                                      |
|-------------------------------|--------------------------------------|
| Connection type               | 1-2. Switch position: Screw terminal |
| Housing material              | Aluminium, Anodized                  |
| Dimension                     | 84 x 90 x 77 mm                      |
| Number of switching positions | 2x Chisel                            |
| Version                       | Safety EN 60204-1                    |
| Operating principle           | 1-2. Switch position: Mechanical     |
| Continuous current            | 1-2. Switch position: 6 A            |
| Rated operating voltage Ue    | 1-2. Switch position: 250 V AC       |
| Installation                  | Horizontal                           |
| Approach direction            | Vertical to mounting surface         |
| Approach speed                | 1-2. Switch position: 40 m/min       |
| Switch position spacing       | 12 mm                                |

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.