


Balluff / BNS 813-B02-R12-61-A-55-0743

Mekanik konum anahtarı

Üretici ürün kodu: BNS02FZ

Seri: BNS



Balluff BNS 813-B02-R12-61-A-55-0743 (BNS02FZ), mekanik konum anahtarı. Bağlantı tipi: 1-2. Switch position: Screw terminal; Gövde malzemesi: Aluminum, Anodized; Boyutlar: 79 x 36 x 77.5 mm.

TEKNİK ÖZELLİKLER

Bağlantı tipi	1-2. Switch position: Screw terminal
Gövde malzemesi	Aluminum, Anodized
Boyutlar	79 x 36 x 77.5 mm
Anahtarlama konumu sayısı	2x Roller
Çalışma prensibi	1. Switch position: Mechanical 2. Switch position: mechanical-inductive
Sürekli akım	1. Switch position: 6 A 2. Switch position: 0.4 A
Anma çalışma gerilimi Ue	1. Switch position: 250 V AC 2. Switch position: 24 V DC
Montaj	Vertical
Yaklaşma yönü	longitudinal, parallel to attachment surface
Yaklaşma hızı	1-2. Switch position: 60 m/min
Anahtarlama konum aralığı	12 mm
Ortam sıcaklığı	-5...85 °C

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

Balluff / BNS 813-B02-R12-61-A-55-0743

Mechanical multiple position limit switches with safety switch positions

Part/model code: BNS02FZ

Series: BNS



Balluff BNS 813-B02-R12-61-A-55-0743 (BNS02FZ): mechanical multiple position limit switches with safety switch positions. Connection type: 1-2. Switch position: Screw terminal; Housing material: Aluminum, Anodized; Dimension: 79 x 36 x 77.5 mm.

TECHNICAL HIGHLIGHTS

Connection type	1-2. Switch position: Screw terminal
Housing material	Aluminum, Anodized
Dimension	79 x 36 x 77.5 mm
Number of switching positions	2x Roller
Operating principle	1. Switch position: Mechanical 2. Switch position: mechanical-inductive
Continuous current	1. Switch position: 6 A 2. Switch position: 0.4 A
Rated operating voltage Ue	1. Switch position: 250 V AC 2. Switch position: 24 V DC
Installation	Vertical
Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-2. Switch position: 60 m/min
Switch position spacing	12 mm
Ambient temperature	-5...85 °C

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.