Balluff / BNS 813-B02-L12-61-A-12-02-S80L

Mekanik konum anahtarı

Üretici ürün kodu: BNS04ZP

Seri: BNS



Balluff BNS 813-B02-L12-61-A-12-02-S80L (BNS04ZP), mekanik konum anahtarı. Bağlantı tipi: 1. Switch position: Konnektör; Gövde malzemesi: Aluminium, Anodized; Anahtarlama konumu sayısı: 2x Roller bearing.

TEKNİK ÖZELLİKLER

Bağlantı tipi	1. Switch position: Konnektör
Gövde malzemesi	Aluminium, Anodized
Anahtarlama konumu sayısı	2x Roller bearing
Sürüm	Safety EN 60204-1
Çalışma prensibi	1-2. Switch position: Mechanical
Sürekli akım	1-2. Switch position: 4 A
Anma çalışma gerilimi Ue	1-2. Switch position: 250 V AC
Montaj	Vertical
Yaklaşma yönü	longitudinal, parallel to attachment surface
Yaklaşma hızı	1-2. Switch position: 120 m/min
Ortam sıcaklığı	-5...85 °C
IP koruma derecesi	IP67

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

Balluff / BNS 813-B02-L12-61-A-12-02-S80L

Mechanical multiple position limit switches with safety switch positions

Part/model code: BNS04ZP

Series: BNS



Balluff BNS 813-B02-L12-61-A-12-02-S80L (BNS04ZP): mechanical multiple position limit switches with safety switch positions. Connection type: 1. Switch position: Connector; Housing material: Aluminium, Anodized; Number of switching positions: 2x Roller bearing.

TECHNICAL HIGHLIGHTS

Connection type	1. Switch position: Connector
Housing material	Aluminium, Anodized
Number of switching positions	2x Roller bearing
Version	Safety EN 60204-1
Operating principle	1-2. Switch position: Mechanical
Continuous current	1-2. Switch position: 4 A
Rated operating voltage Ue	1-2. Switch position: 250 V AC
Installation	Vertical
Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-2. Switch position: 120 m/min
Ambient temperature	-5...85 °C
IP rating	IP67

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.