


Bihl+Wiedemann / BWU4750

AS-Interface bağlantı modülü

Üretici ürün kodu: BWU4750

Seri: AS-Interface



Bihl+Wiedemann BWU4750 (BWU4750), as-interface bağlantı modülü. Tip: Passive distributor AUX; Profil kablo bağlantısı: 1 x AUX 24 V, 1 x AUX 48 V; Bağlantı: 1 x M12-Power cable socket, angled, L coded, 4 kutup.

TEKNİK ÖZELLİKLER

Tip	Passive distributor AUX
Profil kablo bağlantısı	1 x AUX 24 V, 1 x AUX 48 V
Bağlantı	1 x M12-Power cable socket, angled, L coded, 4 kutup
Dahili sigorta	1 A, self-resetting
Yuvarlak kablo	1 m
Yassı tasarım ve kablo kanalına montaj	yes, depth: 25 mm
Gövde	depth: 25 mm
LED durum göstergesi	yes
Koruma derecesi	IP67
Özel işlev	no special function


Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

Bihl+Wiedemann / BWU4750

Passive Distributor AUX to 1 x M12 power cable sockets, angled, L coded, 4 poles, depth 25 mm, IP67

Part/model code: BWU4750

Series: AS-Interface



Bihl+Wiedemann BWU4750 (BWU4750): passive distributor aux to 1 x m12 power cable sockets, angled, l coded, 4 poles, depth 25 mm, ip67. Type: Passive distributor AUX; Profile cable connection: 1 x AUX 24 V, 1 x AUX 48 V; Connection: 1 x M12-Power cable socket, angled, L coded, 4 poles.

TECHNICAL HIGHLIGHTS

Type	Passive distributor AUX
Profile cable connection	1 x AUX 24 V, 1 x AUX 48 V
Connection	1 x M12-Power cable socket, angled, L coded, 4 poles
Internal fuse	1 A, self-resetting
Round cable	1 m
Flat design, installation in cable duct possible	yes, depth: 25 mm
Housing	depth: 25 mm
LED status display	yes
Protection rating	IP67
Special function	no special function

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.