Delta Electronics · ME300

VFD1A5ME43ANSAA

Frekans Sürücüsü

VFD1A5ME43ANSAA, küçük 400 V sınıfı motorlarda 0,4 kW ve 1,5 A HD verileriyle seçilen STO'lu ME300 modelidir. A gövde, düşük güçlü yardımcı bir mekanizmanın pano içinde yerleştirilmesini planlarken kullanılabilecek somut bir seçim bilgisidir.



Üreticinin model kaydındaki ortak gövde görseli. Tam kodun ayrı etiket fotoğrafı değildir; bağlantı ve kapak ayrıntıları değişebilir.

TEKNİK VERİLER

Anma beslemesi	380-480 V AC, 3 faz
Motor kapasitesi (HD tablosu)	0,4 kW
Çıkış akımı (HD)	1,5 A
Gövde / koruma	A / IP20
Dahili EMC filtresi	Yok
STO	Dahili

Akım HD (ağır yük) değeridir. Motor, yük ve ortam birlikte doğrulanır; ND kapasitesi olarak kullanılmaz.

UYGULAMANIZ İÇİN SEÇİM

Küçük motorun gerilim bağlantısını ve güvenli duruş için gerekli arayüzü kontrol edin.

ME43 kodu 230 V tek faz giriş seçeneği midir?

Hayır. Bu kod 380-480 V AC üç faz girişli sürücü sınıfındadır.

TEKLİF TALEBİ

400 V sınıfı yardımcı motorunuzu tanımlayın; kompakt STO'lu seçenek için fiyat hazırlayalım.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Delta Electronics · ME300

VFD1A5ME43ANSAA

Variable Speed Drive

VFD1A5ME43ANSAA is an STO-equipped ME300 selected through its 0.4 kW and 1.5 A HD references for small 400 V class motors. The A frame gives a concrete basis for planning a low-power auxiliary mechanism's cabinet installation.



Shared frame image from the manufacturer model record. Not a separate nameplate photo; terminals and covers may differ.

TECHNICAL DATA

Rated input	380-480 V AC, 3 phase
Motor capacity (HD table)	0.4 kW
Output current (HD)	1.5 A
Frame / protection	A / IP20
Built-in EMC filter	No
STO	Integrated

Current is the HD (heavy-duty) rating. Verify motor, duty and environment together; do not treat it as an ND rating.

SELECTION FOR YOUR APPLICATION

Check the small motor's voltage connection and the interface required for the safe-stop function.

Does ME43 identify a single-phase 230 V input version?

No. This code belongs to the three-phase 380-480 V AC input class.

REQUEST A QUOTATION

Describe the 400 V class auxiliary motor for pricing on the compact STO-equipped option.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.