Delta Electronics · ME300

VFD4A2ME43ANSAA

Frekans Sürücüsü

VFD4A2ME43ANSAA, 1,5 kW sınıfındaki 400 V motor kontrolünde 4,2 A HD kapasite sunan STO'lu ME300'dür. B gövde, küçük bir yardımcı pompa veya mekanizmanın pano yerleşiminde değerlendirilebilir; motor ve yük uygunluğu teklif aşamasında eşleştirilir.



Üreticinin model kaydındaki ortak gövde görseli. Tam kodun ayrı etiket fotoğrafı değildir; bağlantı ve kapak ayrıntıları değişebilir.

TEKNİK VERİLER

Anma beslemesi	380-480 V AC, 3 faz
Motor kapasitesi (HD tablosu)	1,5 kW
Çıkış akımı (HD)	4,2 A
Gövde / koruma	B / IP20
Dahili EMC filtresi	Yok
STO	Dahili

Akım HD (ağır yük) değeridir. Motor, yük ve ortam birlikte doğrulanır; ND kapasitesi olarak kullanılmaz.

UYGULAMANIZ İÇİN SEÇİM

Motor etiketine ek olarak kalkış sıklığını ve uygulanacak hız aralığını paylaşılabilir biçimde kaydedin.

Bu modelde yalnız kW değerini eşleştirmek yeterli midir?

Yeterli değildir. Akım, besleme, yük çevrimi ve istenen donanım özellikleri de doğrulanır.

TEKLİF TALEBİ

1,5 kW motorun çalışma bilgilerini gönderin; B gövdeli STO seçeneği için fiyat alın.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Delta Electronics · ME300

VFD4A2ME43ANSAA

Variable Speed Drive

VFD4A2ME43ANSAA is an STO-equipped ME300 providing 4.2 A HD capacity for the 1.5 kW motor class on 400 V systems. Its B frame can be assessed for a small auxiliary pump or mechanism, subject to motor and load matching.



Shared frame image from the manufacturer model record. Not a separate nameplate photo; terminals and covers may differ.

TECHNICAL DATA

Rated input	380-480 V AC, 3 phase
Motor capacity (HD table)	1.5 kW
Output current (HD)	4.2 A
Frame / protection	B / IP20
Built-in EMC filter	No
STO	Integrated

Current is the HD (heavy-duty) rating. Verify motor, duty and environment together; do not treat it as an ND rating.

SELECTION FOR YOUR APPLICATION

Record starting frequency and intended speed range as well as the motor nameplate data.

Is matching only the kW figure sufficient for this model?

No. Verify current, supply, duty cycle and required hardware features as well.

REQUEST A QUOTATION

Send the 1.5 kW motor operating details for pricing on the B-frame STO option.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.