Delta Electronics · ME300

VFD5A5ME43ANSAA

Frekans Sürücüsü

VFD5A5ME43ANSAA, 2,2 kW motor sınıfında 400 V besleme ve STO gereksinimini bir araya getirir. 5,5 A HD akımı, yardımcı fan veya taşıyıcı motorunun çalışma verileriyle eşleştirilir; C gövde ve harici filtre ihtiyacı ayrıca değerlendirilir.

Üreticinin model kaydındaki ortak gövde görseli. Tam kodun ayrı etiket fotoğrafı değildir; bağlantı ve kapak ayrıntıları değişebilir.

TEKNİK VERİLER

Anma beslemesi	380-480 V AC, 3 faz
Motor kapasitesi (HD tablosu)	2,2 kW
Çıkış akımı (HD)	5,5 A
Gövde / koruma	C / IP20
Dahili EMC filtresi	Yok
STO	Dahili

Akım HD (ağır yük) değeridir. Motor, yük ve ortam birlikte doğrulanır; ND kapasitesi olarak kullanılmaz.

UYGULAMANIZ İÇİN SEÇİM

Hız aralığını, motor akımını ve ortam koşullarını aynı seçim formunda toplayın.

STO'lu modelin çıkış akımı hangi yük sınıfında veriliyor?

Bu ürün paketinde 5,5 A, HD çıkış akımı olarak belirtilmiştir.

TEKLİF TALEBİ

2,2 kW yardımcı motorunuzu tanımlayın; STO'lu C gövdeyi doğru donanım kapsamıyla tekliflendirelim.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Delta Electronics · ME300

VFD5A5ME43ANSAA

Variable Speed Drive

VFD5A5ME43ANSAA brings together 400 V supply and STO requirements in the 2.2 kW motor class. Match its 5.5 A HD current with auxiliary fan or conveyor motor data, reviewing the C frame and external filtering needs separately.

Shared frame image from the manufacturer model record. Not a separate nameplate photo; terminals and covers may differ.

TECHNICAL DATA

Rated input	380-480 V AC, 3 phase
Motor capacity (HD table)	2.2 kW
Output current (HD)	5.5 A
Frame / protection	C / IP20
Built-in EMC filter	No
STO	Integrated

Current is the HD (heavy-duty) rating. Verify motor, duty and environment together; do not treat it as an ND rating.

SELECTION FOR YOUR APPLICATION

Collect speed range, motor current and ambient conditions in the same selection form.

Which duty class applies to the stated output current?

The 5.5 A value in this product package is specified as HD output current.

REQUEST A QUOTATION

Describe the 2.2 kW auxiliary motor for a quotation defining the STO-equipped C-frame hardware scope.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.