Delta Electronics · ME300

VFD7A5ME23ANNAA

Frekans Sürücüsü

VFD7A5ME23ANNAA, üç faz 230 V makine hatlarında 1,5 kW temel kontrol seçeneği olarak incelenebilir. B gövdedeki 7,5 A HD kapasite, motor akımıyla eşleştirilir; STO ve filtre gereksinimleri bu temel koddan ayrı ele alınır.



Üreticinin model kaydındaki ortak gövde görseli. Tam kodun ayrı etiket fotoğrafı değildir; bağlantı ve kapak ayrıntıları değişebilir.

TEKNİK VERİLER

Anma beslemesi	200-240 V AC, 3 faz
Motor kapasitesi (HD tablosu)	1,5 kW
Çıkış akımı (HD)	7,5 A
Gövde / koruma	B / IP20
Dahili EMC filtresi	Yok
STO	Yok

Akım HD (ağır yük) değeridir. Motor, yük ve ortam birlikte doğrulanır; ND kapasitesi olarak kullanılmaz.

UYGULAMANIZ İÇİN SEÇİM

Makinenin mevcut çalıştırma, hız referansı ve durdurma devrelerini tam modelin özellikleriyle karşılaştırın.

Bu ürün tek faz 1,5 kW ME300 ile aynı gövdeyi mi kullanır?

Hayır. Bu üç faz kod B gövdedir; tek faz 1,5 kW seçenekleri C gövdedir.

TEKLİF TALEBİ

Mevcut kontrol bağlantılarınızı iletin; temel 1,5 kW üç faz ME300 için uyum değerlendirelim.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Delta Electronics · ME300

VFD7A5ME23ANNAA

Variable Speed Drive

VFD7A5ME23ANNAA can be assessed as a basic 1.5 kW control option on three-phase 230 V machine circuits. Match its B-frame 7.5 A HD capacity to motor current, considering STO and filtering requirements separately from this basic code.



Shared frame image from the manufacturer model record. Not a separate nameplate photo; terminals and covers may differ.

TECHNICAL DATA

Rated input	200-240 V AC, 3 phase
Motor capacity (HD table)	1.5 kW
Output current (HD)	7.5 A
Frame / protection	B / IP20
Built-in EMC filter	No
STO	No

Current is the HD (heavy-duty) rating. Verify motor, duty and environment together; do not treat it as an ND rating.

SELECTION FOR YOUR APPLICATION

Compare existing run, speed-reference and stop circuits with the exact model's capabilities.

Does it use the same frame as a single-phase 1.5 kW ME300?

No. This three-phase code uses frame B; the single-phase 1.5 kW options use frame C.

REQUEST A QUOTATION

Send the existing control connections for a compatibility review of the basic three-phase 1.5 kW ME300.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.