LAPP · ÖLFLEX® ROBOT 900 P

0028110

Robot torsiyon kablosu

ROBOT 900 P 0028110, 7X0,25 mm² damar yapılı, 6,2 mm çaplı bir robot kablosudur. Bu kesit grubunda nominal gerilim 48 V AC olarak verilir. PUR kılıf ve üreticinin belirttiği burulma yeteneği, düşük gerilimli hareketli bağlantının mekanik şartlarıyla birlikte değerlendirilir.



Üreticinin seri fotoğrafı; kesit, ölçü veya etiket tam sipariş kodunu temsil etmeyebilir.

TEKNİK VERİLER

Damar sayısı x kesit (mm²)	7 X 0.25
Nominal gerilim	48 VAC
Dış çap (mm)	6.2
Kılıf	PUR, siyah
Bakır endeksi (kg/km)	16,8
Ağırlık (kg/km)	48
Yalıtım	TPE

D, kablo dış çapıdır. Ölçüler katalog değerleridir; akım, hareket ve sonlandırma uygunluğu proje koşullarıyla doğrulanır.

UYGULAMANIZ İÇİN SEÇİM

0,25 mm² sürümün 48 V AC sınırını diğer ROBOT 900 P kesitleriyle karıştırmayın.

Bu ürün aynı serinin 300/500 V değeriyle kullanılabilir mi?

Hayır. Kaynak 0,34 mm² ve altındaki grubu 48 V AC olarak ayırır; tam kesit grubunun değeri geçerlidir.

TEKLİF TALEBİ

0028110 için sinyal devresini ve robotun burulma profilini paylaşın.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

LAPP · ÖLFLEX® ROBOT 900 P

0028110

Robot torsion cable

ROBOT 900 P 0028110 has a 7X0.25 mm² layout and a 6.2 mm diameter. The manufacturer assigns 48 V AC to this cross-section group. Evaluate the PUR sheath and stated torsion capability against the mechanical demands of the low-voltage moving connection.



Manufacturer series photograph; size, construction or label may differ from the exact order code.

TECHNICAL DATA

Cores x cross-section (mm²)	7 X 0.25
Rated voltage	48 VAC
Outer diameter (mm)	6.2
Sheath	PUR, black
Copper index (kg/km)	16.8
Weight (kg/km)	48
Insulation	TPE

D is cable outer diameter. Published dimensions do not replace checks of current, motion and termination for the application.

SELECTION FOR YOUR APPLICATION

Keep the 48 V AC limit for this 0.25 mm² version distinct from other ROBOT 900 P sizes.

Can this article use the range's 300/500 V rating?

No. The source separates sizes up to 0.34 mm² as 48 V AC; the rating for the exact size group applies.

REQUEST A QUOTATION

Share the signal circuit and robot torsion profile for 0028110.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.