

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CML730i-T05-2080.R-M12
Işık perdesi verici | 50118937



Sipariş kodu	50118937
Tam model	CML730i-T05-2080.R-M12
Seri	730
Çalışma prensibi	Tek yön çalışma prensibi
Cihaz türü	Verici
İçeriği	BT-2R1 kullanımı için aksesuar
Uygulama	Nesne ölçümü Şeffaf nesnelerin tespiti
Özel versiyon	Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması
İşletme bölgesi	0,1 ... 4 m (emniyetli çalışma mesafesi)
İşletme bölgesi, şeffaf maddeler	0,1 ... 1,75 m
Ölçüm alanının uzunluğu	2.080 mm
Işın sayısı	416 Adet
Işın uzaklığı	5 mm
Işık kaynağı	LED, kızılötesi
Minimum nesne çapı	10 mm

Kaynak: <https://www.leuze.com/tr-tr/cml730i-t05-2080r-m12/50118937>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CML730i-T05-2080.R-M12
Light curtain transmitter | 50118937



Part number	50118937
Full model	CML730i-T05-2080.R-M12
Series	730
Operating principle	Throughbeam principle
Device type	Transmitter
Contains	Accessories for the use of the BT-2R1
Application	Detection of transparent objects Object measurement
Special version	Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning
Operating range	0.1 ... 4 m (guaranteed operating range)
Operating range, transparent media	0.1 ... 1.75 m
Measurement field length	2,080 mm
Number of beams	416 Piece(s)
Beam spacing	5 mm
Light source	LED, Infrared
Minimum object diameter	10 mm

Source: <https://www.leuze.com/en-int/cml730i-t05-2080.r-m12/50118937>

Contact Automation engineering for product selection, supply and commissioning support.