

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CML730i-T10-160.R-M12
Işık perdesi verici | 50118949



Sipariş kodu	50118949
Tam model	CML730i-T10-160.R-M12
Seri	730
Çalışma prensibi	Tek yön çalışma prensibi
Cihaz türü	Verici
İçeriği	BT-2R1 kullanımı için aksesuar
Uygulama	Nesne ölçümü Şeffaf nesnelerin tespiti
Özel versiyon	Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması
İşletme bölgesi	0,3 ... 9,5 m (emniyetli çalışma mesafesi)
İşletme bölgesi, şeffaf maddeler	0,3 ... 3,5 m
Ölçüm alanının uzunluğu	160 mm
Işın sayısı	16 Adet
Işın uzaklığı	10 mm
Işık kaynağı	LED, kızılötesi
Minimum nesne çapı	20 mm

Kaynak: <https://www.leuze.com/tr-tr/cml730i-t10-160r-m12/50118949>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CML730i-T10-160.R-M12
Light curtain transmitter | 50118949



Part number	50118949
Full model	CML730i-T10-160.R-M12
Series	730
Operating principle	Throughbeam principle
Device type	Transmitter
Contains	Accessories for the use of the BT-2R1
Application	Detection of transparent objects Object measurement
Special version	Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning
Operating range	0.3 ... 9.5 m (guaranteed operating range)
Operating range, transparent media	0.3 ... 3.5 m
Measurement field length	160 mm
Number of beams	16 Piece(s)
Beam spacing	10 mm
Light source	LED, Infrared
Minimum object diameter	20 mm

Source: <https://www.leuze.com/en-int/cml730i-t10-160.r-m12/50118949>

Contact Automation engineering for product selection, supply and commissioning support.