

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CML730i-R10-2880.R/CN-M12
Işık perdesi alıcı | 50119103



Sipariş kodu	50119103
Tam model	CML730i-R10-2880.R/CN-M12
Seri	730
Çalışma prensibi	Tek yön çalışma prensibi
Cihaz türü	Alıcı
İçeriği	BT-2R1 kullanımı için aksesuar
Uygulama	Nesne ölçümü Şeffaf nesnelerin tespiti
Özel versiyon	Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması
Ölçüm alanının uzunluğu	2.880 mm
Işın sayısı	288 Adet
Işın uzaklığı	10 mm
Minimum nesne çapı	20 mm
Besleme gerilimi U B	18 ... 30 V, DC
Giriş/çıkış sayısı seçilebilir	2 Adet
Tür	Girişler/çıkışlar seçilebilir

Kaynak: <https://www.leuze.com/tr-tr/cml730i-r10-2880rcn-m12/50119103>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CML730i-R10-2880.R/CN-M12
Light curtain receiver | 50119103



Part number	50119103
Full model	CML730i-R10-2880.R/CN-M12
Series	730
Operating principle	Throughbeam principle
Device type	Receiver
Contains	Accessories for the use of the BT-2R1
Application	Detection of transparent objects Object measurement
Special version	Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning
Measurement field length	2,880 mm
Number of beams	288 Piece(s)
Beam spacing	10 mm
Minimum object diameter	20 mm
Supply voltage U B	18 ... 30 V, DC
Number of inputs/outputs selectable	2 Piece(s)
Type	Inputs/outputs selectable

Source: <https://www.leuze.com/en-int/cml730i-r10-2880.r-cn-m12/50119103>

Contact Automation engineering for product selection, supply and commissioning support.