

# AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CML720i-T20-150.R-M12  
Işık perdesi verici | 50119505



|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Sipariş kodu            | 50119505                                                        |
| Tam model               | CML720i-T20-150.R-M12                                           |
| Seri                    | 720                                                             |
| Çalışma prensibi        | Tek yön çalışma prensibi                                        |
| Cihaz türü              | Verici                                                          |
| İçeriği                 | BT-2R1 kullanımı için aksesuar                                  |
| Uygulama                | Nesne ölçümü                                                    |
| Özel versiyon           | Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması |
| İşletme bölgesi         | 0,3 ... 7 m (emniyetli çalışma mesafesi)                        |
| Ölçüm alanının uzunluğu | 150 mm                                                          |
| Işın sayısı             | 8 Adet                                                          |
| Işın uzaklığı           | 20 mm                                                           |
| Işık kaynağı            | LED, kızılötesi                                                 |
| Minimum nesne çapı      | 30 mm                                                           |
| Besleme gerilimi U B    | 18 ... 30 V, DC                                                 |

Kaynak: <https://www.leuze.com/tr-tr/cml720i-t20-150r-m12/50119505>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

# AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CML720i-T20-150.R-M12  
Light curtain transmitter | 50119505



|                                 |                                                                     |
|---------------------------------|---------------------------------------------------------------------|
| <b>Part number</b>              | 50119505                                                            |
| <b>Full model</b>               | CML720i-T20-150.R-M12                                               |
| <b>Series</b>                   | 720                                                                 |
| <b>Operating principle</b>      | Throughbeam principle                                               |
| <b>Device type</b>              | Transmitter                                                         |
| <b>Contains</b>                 | Accessories for the use of the BT-2R1                               |
| <b>Application</b>              | Object measurement                                                  |
| <b>Special version</b>          | Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning |
| <b>Operating range</b>          | 0.3 ... 7 m (guaranteed operating range)                            |
| <b>Measurement field length</b> | 150 mm                                                              |
| <b>Number of beams</b>          | 8 Piece(s)                                                          |
| <b>Beam spacing</b>             | 20 mm                                                               |
| <b>Light source</b>             | LED, Infrared                                                       |
| <b>Minimum object diameter</b>  | 30 mm                                                               |
| <b>Supply voltage U B</b>       | 18 ... 30 V, DC                                                     |

Source: <https://www.leuze.com/en-int/cml720i-t20-150.r-m12/50119505>

Contact Automation engineering for product selection, supply and commissioning support.