

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CML720i-T20-1750.R-M12
Işık perdesi verici | 50119515



Sipariş kodu	50119515
Tam model	CML720i-T20-1750.R-M12
Seri	720
Çalışma prensibi	Tek yön çalışma prensibi
Cihaz türü	Verici
İçeriği	BT-2R1 kullanımı için aksesuar
Uygulama	Nesne ölçümü
Özel versiyon	Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması
İşletme bölgesi	0,3 ... 7 m (emniyetli çalışma mesafesi)
Ölçüm alanının uzunluğu	1.750 mm
Işın sayısı	88 Adet
Işın uzaklığı	20 mm
Işık kaynağı	LED, kızılötesi
Minimum nesne çapı	30 mm
Besleme gerilimi U B	18 ... 30 V, DC

Kaynak: <https://www.leuze.com/tr-tr/cml720i-t20-1750r-m12/50119515>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CML720i-T20-1750.R-M12
Light curtain transmitter | 50119515



Part number	50119515
Full model	CML720i-T20-1750.R-M12
Series	720
Operating principle	Throughbeam principle
Device type	Transmitter
Contains	Accessories for the use of the BT-2R1
Application	Object measurement
Special version	Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning
Operating range	0.3 ... 7 m (guaranteed operating range)
Measurement field length	1,750 mm
Number of beams	88 Piece(s)
Beam spacing	20 mm
Light source	LED, Infrared
Minimum object diameter	30 mm
Supply voltage U B	18 ... 30 V, DC

Source: <https://www.leuze.com/en-int/cml720i-t20-1750.r-m12/50119515>

Contact Automation engineering for product selection, supply and commissioning support.