

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

IS 218MM/1NC.3-5E0
Endüktif sensör | 50128151



Sipariş kodu	50128151
Tam model	IS 218MM/1NC.3-5E0
Seri	218
Tip. sınır mesafesi S n	5 mm
İşletme bölgesi S a	0 ... 4 mm
Tekrar edilebilirlik	0,5 mm
Koruma devresi	Endüksiyon koruması Kısa devre koruması Ters kutup koruması
Besleme gerilimi U B	10 ... 320 V, AC/DC
Artık dalgalanma	0 ... 20 %, U B 'dan
Açık devre akımı	0 ... 1 mA
Sıcaklık kayması, maks. (% cinsinden başlangıç S r)	10 %, tüm işletme sıcaklığı aralığının üzerinde
Anahtarlama histerezi	20 %
Dijital anahtarlama çıkışı sayısı	1 Adet
Volta j türü	AC/DC
Anahtarlama akımı, maks.	200 mA

Kaynak: <https://www.leuze.com/tr-tr/is-218mm1nc3-5e0/50128151>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

IS 218MM/1NC.3-5E0
Inductive switch | 50128151



Part number	50128151
Full model	IS 218MM/1NC.3-5E0
Series	218
type. operating range limit S n	5 mm
Operating range S a	0 ... 4 mm
Repeatability	0.5 mm
Protective circuit	Inductive protection Polarity reversal protection Short circuit protected
Supply voltage U B	10 ... 320 V, AC/DC
Residual ripple	0 ... 20 %, From U B
Open-circuit current	0 ... 1 mA
Temperature drift, max. (in % of S r)	10 %, Over the entire operating temperature range
Switching hysteresis	20 %
Number of digital switching outputs	1 Piece(s)
Voltage type	AC/DC
Switching current, max.	200 mA

Source: <https://www.leuze.com/en-int/is-218mm-1nc.3-5e0/50128151>

Contact Automation engineering for product selection, supply and commissioning support.