

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CSL710-R05-960.A/L-M12
Işık perdesi alıcı | 50128899



Sipariş kodu	50128899
Tam model	CSL710-R05-960.A/L-M12
Seri	710
Çalışma prensibi	Tek yön çalışma prensibi
Cihaz türü	Alıcı
İçeriği	2 adet somun taşı BT-NC
Uygulama	Hassas nesne tespiti
Özel versiyon	Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması
Ölçüm alanının uzunluğu	960 mm
Işın sayısı	192 Adet
Işın uzaklığı	5 mm
Minimum nesne çapı	10 mm
Koruma devresi	Geçici koruması Kısa devre koruması Ters kutup koruması
Besleme gerilimi U B	18 ... 30 V, DC
Artık dalgalanma	0 ... 15 %, U B 'dan

Kaynak: <https://www.leuze.com/tr-tr/csl710-r05-960al-m12/50128899>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CSL710-R05-960.A/L-M12
Light curtain receiver | 50128899



Part number	50128899
Full model	CSL710-R05-960.A/L-M12
Series	710
Operating principle	Throughbeam principle
Device type	Receiver
Contains	2x BT-NC sliding block
Application	Precise object detection
Special version	Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning
Measurement field length	960 mm
Number of beams	192 Piece(s)
Beam spacing	5 mm
Minimum object diameter	10 mm
Protective circuit	Polarity reversal protection Short circuit protected Transient protection
Supply voltage U B	18 ... 30 V, DC
Residual ripple	0 ... 15 %, From U B

Source: <https://www.leuze.com/en-int/csl710-r05-960.a-l-m12/50128899>

Contact Automation engineering for product selection, supply and commissioning support.