

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

CSL710-T05-1280.A-M12
Işık perdesi verici | 50128991



Sipariş kodu	50128991
Tam model	CSL710-T05-1280.A-M12
Seri	710
Çalışma prensibi	Tek yön çalışma prensibi
Cihaz türü	Verici
İçeriği	2 adet somun taşı BT-NC
Uygulama	Hassas nesne tespiti
Özel versiyon	Paralel ışın taraması Çapraz ışık taraması Çapraz ışın taraması
İşletme bölgesi	0,1 ... 3,5 m (emniyetli çalışma mesafesi)
Sınır mesafesi	0,1 ... 4,5 m (tipik çalışma mesafesi)
Ölçüm alanının uzunluğu	1.280 mm
Işın sayısı	256 Adet
Işın uzaklığı	5 mm
Işık kaynağı	LED, kızılötesi
Dalga boyu	940 nm

Kaynak: <https://www.leuze.com/tr-tr/csl710-t05-1280a-m12/50128991>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

CSL710-T05-1280.A-M12
Light curtain transmitter | 50128991



Part number	50128991
Full model	CSL710-T05-1280.A-M12
Series	710
Operating principle	Throughbeam principle
Device type	Transmitter
Contains	2x BT-NC sliding block
Application	Precise object detection
Special version	Crossed-beam scanning Diagonal-beam scanning Parallel-beam scanning
Operating range	0.1 ... 3.5 m (guaranteed operating range)
Operating range limit	0.1 ... 4.5 m (typical operating range)
Measurement field length	1,280 mm
Number of beams	256 Piece(s)
Beam spacing	5 mm
Light source	LED, Infrared
Wavelength	940 nm

Source: <https://www.leuze.com/en-int/csl710-t05-1280.a-m12/50128991>

Contact Automation engineering for product selection, supply and commissioning support.