

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

LCS-2M30P-N30NNC-K020V
Sensör kapasitif | 50136628



Sipariş kodu	50136628
Tam model	LCS-2M30P-N30NNC-K020V
Seri	LCS-2
Anahtarlama mesafesi S n	2 ... 30 mm
Güvenilir çalışma mesafesi	24,3 mm
Koruma devresi	Kısa devre koruması Ters kutup koruması
Besleme gerilimi U B	10 ... 30 V, DC
Artık dalgalanma	0 ... 10 %
Açık devre akımı	10 mA
Sıcaklık kayması, maks. (% cinsinden başlangıç S r)	10 %
Tekrar edilebilirlik, maks. (% cinsinden başlangıç S r)	5 %
Ölçüm işletmesi akımı	200 mA
Dijital anahtarlama çıkışı sayısı	1 Adet
Tür	Dijital anahtarlama çıkışı
Voltaaj türü	DC

Kaynak: <https://www.leuze.com/tr-tr/lcs-2m30p-n30nn-c-k020v/50136628>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

LCS-2M30P-N30NNC-K020V
Capacitive sensor | 50136628



Part number	50136628
Full model	LCS-2M30P-N30NNC-K020V
Series	LCS-2
Switching distance S n	2 ... 30 mm
Assured switching distance	24.3 mm
Protective circuit	Polarity reversal protection Short circuit protected
Supply voltage U B	10 ... 30 V, DC
Residual ripple	0 ... 10 %
Open-circuit current	10 mA
Temperature drift, max. (in % of S r)	10 %
Repeatability, max. (in % of S r)	5 %
Rated operating current	200 mA
Number of digital switching outputs	1 Piece(s)
Type	Digital switching output
Voltage type	DC

Source: <https://www.leuze.com/en-int/lcs-2m30p-n30nnc-k020v/50136628>

Contact Automation engineering for product selection, supply and commissioning support.