# AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

MLC500T14-600/A
Emniyet ışık perdesi verici | 68006106

| | |
|---|---|
| **Sipariş kodu** | 68006106 |
| **Tam model** | MLC500T14-600/A |
| **Seri** | MLC 500 |
| **Cihaz türü** | Verici |
| **içeriği** | 2 adet somun taşı BT-NC |
| **Uygulama** | Parmak koruması |
| **Tip** | 4, IEC/EN IEC 61496 |
| **SIL** | 3, IEC/EN IEC 62061 |
| **Kullanım süresi** | 20 Yıllar, EN ISO 13849-1 |
| **Çözünürlük** | 14 mm |
| **Koruma alanı yüksekliği** | 600 mm |
| **Çalışma mesafesi** | 0 ... 6 m |
| **Senkronizasyon** | verici ile alıcı arasında optik |
| **Işık kaynağı** | LED, kızılötesi |
| **Dalga boyu** | 940 nm |

Kaynak: https://www.leuze.com/tr-tr/mlc500t14-600a/68006106

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

# AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

MLC500T14-600/A
Safety light curtain transmitter | 68006106

| | |
|---|---|
| **Part number** | 68006106 |
| **Full model** | MLC500T14-600/A |
| **Series** | MLC 500 |
| **Device type** | Transmitter |
| **Contains** | 2x BT-NC sliding block |
| **Application** | Finger protection |
| **Type** | 4, IEC/EN IEC 61496 |
| **SIL** | 3, IEC/EN IEC 62061 |
| **Mission time** | 20 years, EN ISO 13849-1 |
| **Resolution** | 14 mm |
| **Protective field height** | 600 mm |
| **Operating range** | 0 ... 6 m |
| **Synchronization** | Optical between transmitter and receiver |
| **Light source** | LED, Infrared |
| **Wavelength** | 940 nm |

Source: https://www.leuze.com/en-int/mlc500t14-600-a/68006106

Contact Automation engineering for product selection, supply and commissioning support.