

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - TR

MLC520-S-24-1020
Set emniyet sensörü | 68602102



Sipariş kodu	68602102
Tam model	MLC520-S-24-1020
Seri	MLC 520S
Cihaz türü	Set (verici ve alıcı)
İçeriği	4 adet montaj braketli açısı BT-MLC-S-O 6 adet montaj braketli açısı BT-MLC-S-C
Uygulama	Eldiven
İşlevler	Kontaktör izleme (EDM) Otomatik start/restart Start/restart kilidi (RES)
Tip	4, IEC/EN IEC 61496
SIL	3, IEC/EN IEC 62061
Performans Düzeyi (PL)	e, EN ISO 13849-1
PFH D	2,64E-09 Saatte
Kullanım süresi	20 Yıllar, EN ISO 13849-1
Kategori	4, EN ISO 13849
Çözünürlük	24 mm
Koruma alanı yüksekliği	1.020 mm

Kaynak: <https://www.leuze.com/tr-tr/mlc520-s-24-1020/68602102>

Doğru ürün seçimi, tedarik ve devreye alma desteği için Automation mühendislik ekibiyle iletişime geçin.

AUTOMATION | LEUZE TEKNİK ÜRÜN FÖYÜ - EN

MLC520-S-24-1020
Safety sensor set | 68602102



Part number	68602102
Full model	MLC520-S-24-1020
Series	MLC 520S
Device type	Set (transmitter and receiver)
Contains	4x BT-MLC-S-O mounting brackets 6x BT-MLC-S-C mounting brackets
Application	Hand protection
Functions	Automatic start/restart Contactor monitoring (EDM) Start/restart interlock (RES)
Type	4, IEC/EN IEC 61496
SIL	3, IEC/EN IEC 62061
Performance Level (PL)	e, EN ISO 13849-1
PFH D	2,64E-09 per hour
Mission time	20 years, EN ISO 13849-1
Category	4, EN ISO 13849
Resolution	24 mm
Protective field height	1,020 mm

Source: <https://www.leuze.com/en-int/mlc520-s-24-1020/68602102>

Contact Automation engineering for product selection, supply and commissioning support.