Omron · E2B

E2B-M12KN08-WP-B1 2M

Endüktif Sensör

E2B-M12KN08-WP-B1 2M, M12 gövdede 8 mm nominal algılama mesafesiyle hedefe daha fazla açıklık bırakılması gereken tasarımlarda incelenir. Gömülemez yapısı, montaj çevresinde boşluk planlamanızı gerektirir. PNP NO çıkış ve sabit 2 m kablo, kontrol sisteminin giriş mantığına göre doğrudan ürün karşılaştırması yapmanızı sağlar.



Resmî üretici seri/temsil görseli; modelin birebir ölçü veya etiket fotoğrafı olarak kullanılmamalıdır.

TEKNİK VERİLER

Gövde çapı	M12
Nominal algılama mesafesi	8 mm
Çıkış / çalışma	PNP NO
Montaj tipi	Gömülemez / çıkıntılı
Kablo uzunluğu	2 m
Toplam boy	47 mm
Diş uzunluğu	23 mm
Koruma sınıfı	IP67

Algılama mesafesi nominaldir; hedef malzemesi, boyutu ve metal çevre etkileri kontrol edilir.

UYGULAMANIZ İÇİN SEÇİM

Hedef malzemeyi ve yaklaşma yönünü 8 mm nominal referansa göre değerlendirin.

Daha uzun mesafe her montajda daha iyi seçim midir?

Montaj alanı, hedef boyutu ve algılama kararlılığı birlikte değerlendirilir; mesafe tek seçim ölçütü değildir.

TEKLİF TALEBİ

M12 KN08 için hedef parça bilginizle seçim teklifi alın.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · E2B

E2B-M12KN08-WP-B1 2M

Inductive Sensor

E2B-M12KN08-WP-B1 2M offers 8 mm nominal sensing in an M12 body for layouts needing additional target clearance. Its non-flush design requires surrounding space. PNP NO output and a fixed 2 m cable make signal and connection comparisons straightforward.



Official manufacturer family/representative visual; not an exact dimensional or nameplate photograph.

TECHNICAL DATA

Body size	M12
Nominal sensing distance	8 mm
Output / operation	PNP NO
Mounting type	Non-flush
Cable length	2 m
Overall length	47 mm
Thread length	23 mm
Ingress protection	IP67

Sensing distance is nominal; check target material, size and surrounding metal effects.

SELECTION FOR YOUR APPLICATION

Assess target material and approach direction against the 8 mm nominal reference.

Is a longer sensing distance always preferable?

Mounting space, target size and detection stability also matter; distance is only one selection criterion.

REQUEST A QUOTATION

Request M12 KN08 selection with target-part details.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.