Omron · E2B

E2B-M12LN08-WP-B1 2M

Endüktif Sensör

E2B-M12LN08-WP-B1 2M, 70 mm toplam boylu M12 gövdeyi 8 mm nominal algılama ve PNP NO çıkışla birleştirir. 46 mm diş uzunluğu, daha uzun montaj mesafesi gereken yerlerde çizim bazında karşılaştırma sağlar. 2 m kablolu sensörün gömülemez ucunu çevre metallerden ayıracak yerleşim ayrıca doğrulanmalıdır.



Resmî üretici seri/temsil görseli; modelin birebir ölçü veya etiket fotoğrafı olarak kullanılmamalıdır.

TEKNİK VERİLER

Gövde çapı	M12
Nominal algılama mesafesi	8 mm
Çıkış / çalışma	PNP NO
Montaj tipi	Gömülemez / çıkıntılı
Kablo uzunluğu	2 m
Toplam boy	70 mm
Diş uzunluğu	46 mm
Koruma sınıfı	IP67

Algılama mesafesi nominaldir; hedef malzemesi, boyutu ve metal çevre etkileri kontrol edilir.

UYGULAMANIZ İÇİN SEÇİM

Montaj somunlarının yerini 46 mm diş uzunluğu ve gerçek braketle karşılaştırın.

Uzun gövde daha uzun algılama mesafesi demek midir?

Tek başına değildir; bu modelin nominal mesafesi 8 mm'dir ve gövde boyundan ayrı bir özelliktir.

TEKLİF TALEBİ

Uzun M12 gövde gerektiren noktanız için bu kodla teklif isteyin.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · E2B

E2B-M12LN08-WP-B1 2M

Inductive Sensor

E2B-M12LN08-WP-B1 2M combines a 70 mm overall M12 body with 8 mm nominal sensing and PNP NO output. Its 46 mm thread length supports drawing-based comparison where a longer mounting reach is needed. Verify a non-flush installation that separates the sensing tip from surrounding metal; the cable is 2 m.



Official manufacturer family/representative visual; not an exact dimensional or nameplate photograph.

TECHNICAL DATA

Body size	M12
Nominal sensing distance	8 mm
Output / operation	PNP NO
Mounting type	Non-flush
Cable length	2 m
Overall length	70 mm
Thread length	46 mm
Ingress protection	IP67

Sensing distance is nominal; check target material, size and surrounding metal effects.

SELECTION FOR YOUR APPLICATION

Compare nut positions against the 46 mm thread length and the actual bracket.

Does a longer body necessarily mean longer sensing range?

No; this model's nominal range is 8 mm, a specification separate from body length.

REQUEST A QUOTATION

Request this code for the point requiring a long M12 body.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.