Omron · E2B

E2B-M12LS04-WP-C1 2M

Endüktif Sensör

E2B-M12LS04-WP-C1 2M, uzun M12 gövdede 4 mm nominal mesafe ve NPN NO çıkış sunar. 70 mm toplam boy, 53 mm diş uzunluğu ve 2 m kablo bağlantısı montaj teklifini ölçüyle hazırlamaya yardımcı olur. Resmi kayıttaki yarı gömülebilir yapı, tam gömme kabul edilmeden teknik çizimle eşleştirilmelidir.



Resmî üretici seri/temsil görseli; modelin birebir ölçü veya etiket fotoğrafı olarak kullanılmamalıdır.

TEKNİK VERİLER

Gövde çapı	M12
Nominal algılama mesafesi	4 mm
Çıkış / çalışma	NPN NO
Montaj tipi	Yarı gömülebilir
Kablo uzunluğu	2 m
Toplam boy	70 mm
Diş uzunluğu	53 mm
Koruma sınıfı	IP67

Algılama mesafesi nominaldir; hedef malzemesi, boyutu ve metal çevre etkileri kontrol edilir.

UYGULAMANIZ İÇİN SEÇİM

Yarı gömülebilir montaj sınırını braket kalınlığı ve yüzey konumuyla kontrol edin.

Yarı gömülebilir ifade tam gömme ile aynı mıdır?

Aynı kabul edilmez; üreticinin izin verdiği metal çevre ve yüzey yerleşimi esas alınır.

TEKLİF TALEBİ

Uzun gövde ve NPN çıkış ihtiyacınız için bu modeli fiyatlandırın.

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · E2B

E2B-M12LS04-WP-C1 2M

Inductive Sensor

E2B-M12LS04-WP-C1 2M offers 4 mm nominal range and NPN NO output in a long M12 body. Its 70 mm overall length, 53 mm thread and 2 m cable help define a dimensioned mounting enquiry. Match the official quasi-flush classification to the drawing without assuming fully flush installation.



Official manufacturer family/representative visual; not an exact dimensional or nameplate photograph.

TECHNICAL DATA

Body size	M12
Nominal sensing distance	4 mm
Output / operation	NPN NO
Mounting type	Quasi-flush
Cable length	2 m
Overall length	70 mm
Thread length	53 mm
Ingress protection	IP67

Sensing distance is nominal; check target material, size and surrounding metal effects.

SELECTION FOR YOUR APPLICATION

Check quasi-flush mounting limits against bracket thickness and face position.

Is quasi-flush the same as fully flush mounting?

Do not treat them as identical; follow the manufacturer's metal-clearance and face-position requirements.

REQUEST A QUOTATION

Have this model priced for a long-body NPN output requirement.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.