Omron · E2B

E2B-M18KN16-WP-B2 2M

Endüktif Sensör

E2B-M18KN16-WP-B2 2M, 16 mm nominal mesafeyi M18 gövde ve PNP NC çıkışla sunar. 56 mm toplam boylu, 2 m kablolu sensör, daha uzak metal hedeflerin konum kontrolünde değerlendirmeye alınabilir. Nominal mesafenin hedefin malzemesi ve boyutuyla ilişkili olduğunu bilmek, gerçek çalışma boşluğunu doğru tanımlamaya yardımcı olur.



Resmî üretici seri/temsil görseli; modelin birebir ölçü veya etiket fotoğrafı olarak kullanılmamalıdır.

TEKNİK VERİLER

Gövde çapı	M18
Nominal algılama mesafesi	16 mm
Çıkış / çalışma	PNP NC
Montaj tipi	Gömülemez / çıkıntılı
Kablo uzunluğu	2 m
Toplam boy	56 mm
Diş uzunluğu	26 mm
Koruma sınıfı	IP67

Algılama mesafesi nominaldir; hedef malzemesi, boyutu ve metal çevre etkileri kontrol edilir.

UYGULAMANIZ İÇİN SEÇİM

Hedefin malzemesini, yüzey boyutunu ve yaklaşma yönünü paylaşın.

16 mm değeri her metal parçada kesin algılama boşluğu mudur?

Hayır. Nominal değer standart koşullara dayanır; gerçek hedef ve montajla doğrulama gerekir.

TEKLİF TALEBİ

PNP NC çıkışlı geniş mesafeli M18 seçiminiz için teklif isteyin.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · E2B

E2B-M18KN16-WP-B2 2M

Inductive Sensor

E2B-M18KN16-WP-B2 2M provides a 16 mm nominal range with an M18 body and PNP NC output. The 56 mm overall sensor with a 2 m cable can be assessed for more distant metal-position targets. Relating nominal range to target material and size helps establish the actual working gap.



Official manufacturer family/representative visual; not an exact dimensional or nameplate photograph.

TECHNICAL DATA

Body size	M18
Nominal sensing distance	16 mm
Output / operation	PNP NC
Mounting type	Non-flush
Cable length	2 m
Overall length	56 mm
Thread length	26 mm
Ingress protection	IP67

Sensing distance is nominal; check target material, size and surrounding metal effects.

SELECTION FOR YOUR APPLICATION

Share target material, face dimensions and approach direction.

Is 16 mm a guaranteed sensing gap for every metal component?

No. Nominal range is based on reference conditions; verify it with the real target and mounting.

REQUEST A QUOTATION

Request an offer for the longer-range M18 PNP NC selection.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.