Omron · E2B

E2B-M30KS10-WP-C1 2M

Endüktif Sensör

E2B-M30KS10-WP-C1 2M, M30 çapta gömülebilir montaj isteyen bir noktada 10 mm nominal algılama ve NPN NO çıkışla incelenebilir. 60 mm toplam boy, 41 mm diş uzunluğu ve 2 m kablo ürün eşleştirmesinin ana ölçüleridir. Algılama ucunun darbe alabileceği düzenlerde mekanik koruma ayrıca tasarlanmalıdır.



Resmî üretici seri/temsil görseli; modelin birebir ölçü veya etiket fotoğrafı olarak kullanılmamalıdır.

TEKNİK VERİLER

Gövde çapı	M30
Nominal algılama mesafesi	10 mm
Çıkış / çalışma	NPN NO
Montaj tipi	Gömülebilir
Kablo uzunluğu	2 m
Toplam boy	60 mm
Diş uzunluğu	41 mm
Koruma sınıfı	IP67

Algılama mesafesi nominaldir; hedef malzemesi, boyutu ve metal çevre etkileri kontrol edilir.

UYGULAMANIZ İÇİN SEÇİM

Algılama yüzeyinin metal hedefle temas etmeyeceği çalışma boşluğunu belirleyin.

Gömülebilir sensörün hedefe sürtmesi normal kullanım sayılır mı?

Hayır; endüktif algılama temassızdır, mekanik temas ve darbe ayrıca önlenmelidir.

TEKLİF TALEBİ

Gömülebilir M30 NPN sensör ihtiyacınız için bu kodla fiyat isteyin.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · E2B

E2B-M30KS10-WP-C1 2M

Inductive Sensor

For an M30 flush-mounting point, review E2B-M30KS10-WP-C1 2M at 10 mm nominal range with NPN NO output. Overall length of 60 mm, 41 mm thread and a 2 m cable are key matching dimensions. Design separate mechanical protection where the sensing face could be struck.



Official manufacturer family/representative visual; not an exact dimensional or nameplate photograph.

TECHNICAL DATA

Body size	M30
Nominal sensing distance	10 mm
Output / operation	NPN NO
Mounting type	Flush
Cable length	2 m
Overall length	60 mm
Thread length	41 mm
Ingress protection	IP67

Sensing distance is nominal; check target material, size and surrounding metal effects.

SELECTION FOR YOUR APPLICATION

Establish a working gap that prevents target contact with the sensing face.

Is rubbing against the target normal for a flush sensor?

No; inductive detection is contactless, and mechanical contact or impact must be prevented separately.

REQUEST A QUOTATION

Request pricing for this flush M30 NPN sensor code.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.