
Omron · E2B

E2B-S08KS01-WP-B1 2M

Endüktif Sensör

E2B-S08KS01-WP-B1 2M, M8 gövdede 1,5 mm nominal algılama ve PNP NO çıkışla yakın metal konumları için değerlendirilebilir. Gömülebilir tipin toplam boyu 42 mm, diş uzunluğu 27 mm ve kablosu 2 m'dir. Küçük çalışma boşluğunda mekanik toleransların ölçülmesi, sahada kararlı algılama hedefinin önemli bir parçasıdır.



Resmî üretici seri/temsil görseli; modelin birebir ölçü veya etiket fotoğrafı olarak kullanılmamalıdır.

TEKNİK VERİLER

Gövde çapı	M8
Nominal algılama mesafesi	1.5 mm
Çıkış / çalışma	PNP NO
Montaj tipi	Gömülebilir
Kablo uzunluğu	2 m
Toplam boy	42 mm
Diş uzunluğu	27 mm
Koruma sınıfı	IP67

Algılama mesafesi nominaldir; hedef malzemesi, boyutu ve metal çevre etkileri kontrol edilir.

UYGULAMANIZ İÇİN SEÇİM

Hedefin hareketindeki mekanik toleransı algılama boşluğuyla birlikte değerlendirin.

Model kodundaki 01 ifadesi mesafenin tam 1 mm olduğunu mu gösterir?

Bu modelin resmi nominal algılama mesafesi 1,5 mm'dir; teknik veri esas alınmalıdır.

TEKLİF TALEBİ

Yakın mesafe M8 algılama noktanızın ölçüleriyle teklif isteyin.

Resmî ürün kaydı · Üretici dokümanı


Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · E2B

E2B-S08KS01-WP-B1 2M

Inductive Sensor

E2B-S08KS01-WP-B1 2M can be assessed for close metal positions with an M8 body, 1.5 mm nominal range and PNP NO output. The flush model has a 42 mm overall length, 27 mm thread and 2 m cable. Measuring mechanical tolerances is important when defining a small, stable sensing gap.



Official manufacturer family/representative visual; not an exact dimensional or nameplate photograph.

TECHNICAL DATA

Body size	M8
Nominal sensing distance	1.5 mm
Output / operation	PNP NO
Mounting type	Flush
Cable length	2 m
Overall length	42 mm
Thread length	27 mm
Ingress protection	IP67

Sensing distance is nominal; check target material, size and surrounding metal effects.

SELECTION FOR YOUR APPLICATION

Evaluate target-motion tolerances together with the intended sensing gap.

Does 01 in the code mean a sensing range of exactly 1 mm?

The official nominal range of this model is 1.5 mm; use the technical data rather than that assumption.

REQUEST A QUOTATION

Request an offer with dimensions from the close-range M8 sensing point.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.