Omron · S8VK-S

# S8VK-S06024

Güç Kaynağı

S8VK-S06024, 60 W gücü 24 V DC ve 2,5 A çıkışla kompakt DIN ray gövdede sunar. 90 mm derinlik, pano kapağına yakın yerleşimlerde değerlendirilecek somut bir ölçüdür. Push-in terminaller, vidalı bağlantıdan farklı kablolama yaklaşımı isteyen tasarımlarda S serisini karşılaştırmak için belirgin bir özellik sağlar.




Üreticinin bu ürün sayfasında kullandığı resmî ürün görseli.

## TEKNİK VERİLER

| | |
|---|---|
| Nominal AC giriş | 100-240 V AC, tek faz |
| DC çıkış gerilimi | 24 V DC |
| Güç sınıfı | 60 W |
| Nominal çıkış akımı | 2,5 A |
| Terminal tipi | Push-in |
| Montaj | DIN ray |
| Genişlik x yükseklik x derinlik | 32 mm x 90 mm x 90 mm |

Nominal çıkış ve güç sınıfı üretici verileridir. Sıcaklık/yerleşim kapasite düşümü ile açılış yükü ayrıca incelenir.

## UYGULAMANIZ İÇİN SEÇİM

90 mm derinliğe ilave kablo payını ve sürekli yük ihtiyacını planlayın.

### G06024 ile yalnız seri adı mı değişir?

Terminal tipi ve gövde derinliği gibi özellikler farklıdır; teknik tablolar birlikte karşılaştırılmalıdır.

### TEKLİF TALEBİ

S06024 için kompakt pano yerleşiminize göre fiyat isteyin.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Omron · S8VK-S

# S8VK-S06024

Power Supply

S8VK-S06024 provides 60 W at 24 V DC, 2.5 A in a compact DIN-rail body. Its 90 mm depth is useful when assessing door clearance. Push-in terminals distinguish its wiring approach from screw-terminal alternatives.




Official product visual used on the manufacturer product page.

## TECHNICAL DATA

| | |
|---|---|
| Nominal AC input | 100-240 V AC, single phase |
| DC output voltage | 24 V DC |
| Power class | 60 W |
| Rated output current | 2.5 A |
| Terminal type | Push-in |
| Mounting | DIN rail |
| Width x height x depth | 32 mm x 90 mm x 90 mm |

Rated output and power class are manufacturer values. Review temperature/mounting derating and startup load separately.

### SELECTION FOR YOUR APPLICATION

Plan cable allowance beyond the 90 mm depth and check continuous load demand.

**Is the series name the only difference from G06024?**

Terminal type and body depth are among the differences, so compare both technical tables.

### REQUEST A QUOTATION

Request S06024 for the compact cabinet layout.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.