# ReeR / MICRON MI 305 AV

Ölçüm ışık perdesi

**Üretici ürün kodu: 1250081**

Seri: MICRON

ReeR MICRON MI 305 AV (1250081), ölçüm ışık perdesi. Kontrol edilen yükseklik (mm): 250; Azami aralık (m): 18; Çalışma sıcaklığı (°C): - 10 ... 55.

## TEKNİK ÖZELLİKLER

| | |
|---|---|
| **Kontrol edilen yükseklik (mm)** | 250 |
| **Azami aralık (m)** | 18 |
| **Çalışma sıcaklığı (°C)** | - 10 ... 55 |
| **Işın sayısı** | 6 |
| **Sinyalizasyon** | LEDs for light curtain's status ve diagnostics |
| **Bağlantılar** | M12 5-pole connector (emitter), M12 8-pole connector (receiver), M5 4-pole connector for programming interface |
| **Çıkışlar** | 2 analog outputs (0-10 VDC) with programmable functions + 2 solid state 0 or 24 V programmable digital outputs (PNP 100 mA at 24 VDC) |
| **Programlanabilirlik** | Evet |
| **Çıkış tipi** | 2 analog outputs (0-10 VDC) |
| **Besleme (VDC)** | 24 ± 20% |
| **Işın aralığı (mm)** | 50 |
| **Toplam yükseklik (mm)** | 363 |

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

# ReeR / MICRON MI 305 AV

Measurement light curtain

**Part/model code: 1250081**

Series: MICRON

ReeR MICRON MI 305 AV (1250081): measurement light curtain. Controlled height (mm): 250; Max. range (m): 18; Operating temperature (°C): - 10 ... 55.

## TECHNICAL HIGHLIGHTS

| | |
|---|---|
| **Controlled height (mm)** | 250 |
| **Max. range (m)** | 18 |
| **Operating temperature (°C)** | - 10 ... 55 |
| **Number of beams** | 6 |
| **Signalling** | LEDs for light curtain's status and diagnostics |
| **Connections** | M12 5-pole connector (emitter), M12 8-pole connector (receiver), M5 4-pole connector for programming interface |
| **Outputs** | 2 analog outputs (0-10 VDC) with programmable functions + 2 solid state 0 or 24 V programmable digital outputs (PNP 100 mA at 24 VDC) |
| **Programmability** | Yes |
| **Outputs type** | 2 analog outputs (0-10 VDC) |
| **Power supply (VDC)** | 24 ± 20% |
| **Beam spacing (mm)** | 50 |
| **Overall height (mm)** | 363 |

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.