ReeR / MICRON MI 755 AV

Ölçüm ışık perdesi

Üretici ürün kodu: 1250084

Seri: MICRON

ReeR MICRON MI 755 AV (1250084), ölçüm ışık perdesi. Kontrol edilen yükseklik (mm): 700; Azami aralık (m): 18; Çalışma sıcaklığı (°C): - 10 ... 55.

TEKNİK ÖZELLİKLER

Kontrol edilen yükseklik (mm)	700
Azami aralık (m)	18
Çalışma sıcaklığı (°C)	- 10 ... 55
Işın sayısı	15
Sinyalizasyon	LEDs for light curtain's status ve diagnostics
Bağlantılar	M12 5-pole connector (emitter), M12 8-pole connector (receiver), M5 4-pole connector for programming interface
Çıkışlar	2 analog outputs (0-10 VDC) with programmable functions + 2 solid state 0 or 24 V programmable digital outputs (PNP 100 mA at 24 VDC)
Programlanabilirlik	Evet
Çıkış tipi	2 analog outputs (0-10 VDC)
Besleme (VDC)	24 ± 20%
Işın aralığı (mm)	50
Toplam yükseklik (mm)	813

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

ReeR / MICRON MI 755 AV

Measurement light curtain

Part/model code: 1250084

Series: MICRON

ReeR MICRON MI 755 AV (1250084): measurement light curtain. Controlled height (mm): 700; Max. range (m): 18; Operating temperature (°C): - 10 ... 55.

TECHNICAL HIGHLIGHTS

Controlled height (mm)	700
Max. range (m)	18
Operating temperature (°C)	- 10 ... 55
Number of beams	15
Signalling	LEDs for light curtain's status and diagnostics
Connections	M12 5-pole connector (emitter), M12 8-pole connector (receiver), M5 4-pole connector for programming interface
Outputs	2 analog outputs (0-10 VDC) with programmable functions + 2 solid state 0 or 24 V programmable digital outputs (PNP 100 mA at 24 VDC)
Programmability	Yes
Outputs type	2 analog outputs (0-10 VDC)
Power supply (VDC)	24 ± 20%
Beam spacing (mm)	50
Overall height (mm)	813

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.