

ReeR / SR TC

Endüstriyel emniyet bileşeni

Üretici ürün kodu: 1330810

Seri: SR



ReeR SR TC (1330810), endüstriyel emniyet bileşeni. Emniyet seviyesi: PL e; Emniyet seviyesi (SIL / PL): PL e - SIL 3 - SILCL 3 - Cat. 4 - Type III C (EN 574); Çalışma sıcaklığı (°C): -30 ... +55.

TEKNİK ÖZELLİKLER

Emniyet seviyesi	PL e
Emniyet seviyesi (SIL / PL)	PL e - SIL 3 - SILCL 3 - Cat. 4 - Type III C (EN 574)
Çalışma sıcaklığı (°C)	-30 ... +55
Response time (ms)	≤ 20
Sinyalizasyon	LEDs indication for status ve diagnostic: power supply, channel 1 ve channel 2
Bağlantılar	Removable terminal blocks, clamp contacts
MTTFD (ISO 13849), yıl	The values depend on the type of use. Refer to the technical manual
PFHD (IEC 61508)	The values depend on the type of use. Refer to the technical manual
Bağlanabilir emniyet cihazları	Two hand scontrol safety devices
24 VDC'de asgari anahtarlama akımı (mA)	6
Simultaneity (s)	≤ 0,5
Emniyet rölesi çıkışları	2 Normalde açık (NO) (6A at 250 VAC)

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

ReeR / SR TC

Safety automation component

Part/model code: 1330810

Series: SR



ReeR SR TC (1330810): safety automation component. Safety level: PL e; Safety level (SIL / PL): PL e - SIL 3 - SILCL 3 - Cat. 4 - Type III C (EN 574); Operating temperature (°C): -30 ... +55.

TECHNICAL HIGHLIGHTS

Safety level	PL e
Safety level (SIL / PL)	PL e - SIL 3 - SILCL 3 - Cat. 4 - Type III C (EN 574)
Operating temperature (°C)	-30 ... +55
Response time (ms)	≤ 20
Signalling	LEDs indication for status and diagnostic: power supply, channel 1 and channel 2
Connections	Removable terminal blocks, clamp contacts
MTTFD (ISO13849) years	The values depend on the type of use. Refer to the technical manual
PFHD (IEC 61508)	The values depend on the type of use. Refer to the technical manual
Safety devices to be connected	Two hand scontrol safety devices
Min. switching current at 24 VDC (mA)	6
Simultaneity (s)	≤ 0,5
Safety relay outputs	2 NO (6A at 250 VAC)

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.