

ReeR / UAM-05LP-T301C

Endüstriyel emniyet bileşeni

Üretici ürün kodu: 1350101

Seri: UAM-05LP-T301C



ReeR UAM-05LP-T301C (1350101), endüstriyel emniyet bileşeni. Bağlantı tipi: Konnektör; Emniyet seviyesi: PL d; Restart: Integrated ve seçilebilir.

TEKNİK ÖZELLİKLER

Bağlantı tipi	Konnektör
Emniyet seviyesi	PL d
Restart	Integrated ve seçilebilir
Emniyet seviyesi (SIL / PL)	SIL 2 - SILCL 2 - PL d - Cat. 3
Çalışma sıcaklığı (°C)	- 10 ... 50
Response time (ms)	OFF 60 ... 510 / ON 270 ... 510
Sensör tipi	Laser scanner
Bağlantılar	Konnektör with cable (30 cm)
PFHD (IEC 61508)	1,6E-07 (T1 = 20 yıl) (master/slave function used)
Safety zone min. target reflectivity	10% at 20 m
Safety zone resolution (mm)	30 mm maks. 1,8 m - 50 mm maks. 3 m - 70 mm maks. 5 m
Warning zone min. target reflectivity	20% at 15 m

Seçili üretici değerleridir; kaynakta belirtilen koşullar ve dipnotlar geçerlidir. Üretici görseli teslim edilen varyanttan farklı olabilir. Automation özeti orijinal dokümantasyonun yerine geçmez.

ReeR / UAM-05LP-T301C

Safety automation component

Part/model code: 1350101

Series: UAM-05LP-T301C



ReeR UAM-05LP-T301C (1350101): safety automation component. Connection type: Connector; Safety level: PL d; Restart: Integrated and selectable.

TECHNICAL HIGHLIGHTS

Connection type	Connector
Safety level	PL d
Restart	Integrated and selectable
Safety level (SIL / PL)	SIL 2 - SILCL 2 - PL d - Cat. 3
Operating temperature (°C)	- 10 ... 50
Response time (ms)	OFF 60 ... 510 / ON 270 ... 510
Sensor type	Laser scanner
Connections	Connector with cable (30 cm)
PFHD (IEC 61508)	1,6E-07 (T1 = 20 years) (master/slave function used)
Safety zone min. target reflectivity	10% at 20 m
Safety zone resolution (mm)	30 mm max. 1,8 m - 50 mm max. 3 m - 70 mm max. 5 m
Warning zone min. target reflectivity	20% at 15 m

Selected manufacturer values; source conditions and footnotes apply. The manufacturer illustration may differ from the delivered variant. This Automation summary does not replace the original documentation.