

SICK / DFV60A-22PC65536

Ölçüm tekerlekli enkoder

Sipariş kodu: 1051309

Üretici: SICK AG | Seri: DFV60



SICK DFV60A-22PC65536 (1051309), ölçüm tekerlekli enkoder. Bağlantı tipi: Erkek konnektör, M12, 8-pin, radial; Besleme gerilimi: 4.5 V ... 32 V; Koruma derecesi: IP65.

TEKNİK ÖZELLİKLER

Bağlantı tipi	Erkek konnektör, M12, 8-pin, radial
Besleme gerilimi	4.5 V ... 32 V
Koruma derecesi	IP65
Tur başına darbe sayısı	65,536
Hata sınırları	± 4 mm/m, ölçüm tekerleğine bağlı (ölçüm tekerleği yüzeyi + ölçüm yüzeyi + ortam koşulları)
Başlatma süresi	30 ms
İletişim arayüzü	Artımlı
İletişim arayüzü ayrıntısı	TTL / HTL
Gövde	Alüminyum
Başlangıç torku	0.8 Ncm (at 20 °C)
Çalışma torku	0.6 Ncm (at 20 °C)
Çalışma hızı	1,500 min ⁻¹
EMC	Uyarınca EN 61000-6-2 and EN 61000-6-4

Seçili teknik değerlerdir; numaralı işaretler bağlantısı verilen orijinal üretici föyündeki dipnotlara gönderme yapar. Görsel ilgili modelin üretici belgesinden alınmıştır ve teslim edilen varyanttan farklı olabilir. Bu Automation özeti üretici belgesi değildir.

SICK / DFV60A-22PC65536

Measuring wheel encoders

Part number: 1051309

Manufacturer: SICK AG | Series: DFV60



SICK DFV60A-22PC65536 (1051309): measuring wheel encoders. Connection type: Male connector, M12, 8-pin, radial; Supply voltage: 4.5 V ... 32 V; Enclosure rating: IP65.

TECHNICAL HIGHLIGHTS

Connection type	Male connector, M12, 8-pin, radial
Supply voltage	4.5 V ... 32 V
Enclosure rating	IP65
Pulses per revolution	65,536
Error limits	± 4 mm/m, subject to measuring wheel (measuring wheel surface + measuring surface + ambient conditions)
Initialization time	30 ms
Communication interface	Incremental
Communication Interface detail	TTL / HTL
Housing	Aluminum
Start up torque	0.8 Ncm (at 20 °C)
Operating torque	0.6 Ncm (at 20 °C)
Operating speed	1,500 min ⁻¹
EMC	According to EN 61000-6-2 and EN 61000-6-4

Selected technical values; numbered marks refer to the linked original manufacturer data sheet. The product illustration is taken from the exact-model manufacturer document and may differ from the delivered variant. This Automation summary is not a manufacturer-issued data sheet.