Tele Radio · Analog Modüller

D8-2

Analog Çıkış Modülü

D8-2, 0-10 V sinyal çıkışı için listelenen analog çıkış modülüdür. 5-24 V DC besleme ve 113 × 38 × 53 mm gövde, kontrol sistemindeki yerleşim ve güç planıyla birlikte değerlendirilir. Giriş modülü D8-1 ile aynı görevde kullanılmaz.



Üreticinin D8-2 kaydına bağlı temsilî ürün fotoğrafı; frekans etiketi ve teslim konfigürasyonu ayrıca teyit edilir.

TEKNİK VERİLER

Besleme seçenekleri	5-24 V DC
Analog çıkış	0-10 V
Koruma sınıfı	IP65
Ağırlık	200 g
Ölçüler (G x Y x D)	113 x 38 x 53 mm
Çalışma sıcaklığı	-20 / +55 °C

Teknik değerler resmî model kaydındandır. Besleme seçenekleri ve sistem uyumu siparişte teyit edilir.

UYGULAMANIZ İÇİN SEÇİM

0-10 V kabul eden hedef girişin yük koşullarını ve sistem bağlantısını doğrulayın.

4-20 mA çıkışı olduğu varsayılabilir mi?

Hayır. Bu kayıt 0-10 V çıkış belirtir; başka sinyal türleri için ayrıca doğrulanmış çözüm gerekir.

TEKLİF TALEBİ

D8-2 için bağlanacak cihazın analog giriş verisini paylaşın; çıkış modülünü uygun kapsamla teklif edelim.

Resmî ürün kaydı · Üretici dokümanı

Automation tarafından resmî kaynaklarla hazırlanmıştır; üreticinin orijinal föyü değildir. Fiyat, stok ve termin teyit edilir.

Tele Radio · Analog Modüller

D8-2

Analog Output Module

D8-2 is an analog output module listed for a 0-10 V signal. Its 5-24 V DC supply and 113 × 38 × 53 mm housing must be assessed with the control system's power and mounting plan. It does not perform the same role as the D8-1 input module.



Manufacturer image assigned to D8-2; illustrative. Verify frequency label and delivered configuration separately.

TECHNICAL DATA

Listed supply options	5-24 V DC
Analog output	0-10 V
Protection rating	IP65
Weight	200 g
Dimensions (W x H x D)	113 x 38 x 53 mm
Operating temperature	-20 / +55 °C

Technical values follow the official model record. Confirm supply options and system compatibility when ordering.

SELECTION FOR YOUR APPLICATION

Verify the load requirements of the destination's 0-10 V input and the system connection.

Can a 4-20 mA output be assumed?

No. This record specifies 0-10 V; other signal types require a separately verified solution.

REQUEST A QUOTATION

Share the target device's analog-input data for an appropriately scoped D8-2 offer.

Manufacturer product record · Manufacturer document

Automation summary based on official sources; not a manufacturer-issued datasheet. Price, stock and lead time require confirmation.