# Yılmaz Redüktör NR173 Flanşlı Helisel Redüktör

## TEMEL MODEL / NR173

NR173, N17 grubunun üç kademeli flanşlı helisel tahrik modelidir. Besleme veya dozaj mekanizmasında kullanılacaksa redüktör seçiminde hedef üretim hızının mekanik çıkış devrine çevrilmesi gerekir. Malzeme miktarı, çevrim sayısı veya hareket mesafesi gibi proses verilerini paylaşarak gerekli oranı tanımlayan daha anlamlı bir teklif hazırlatabilirsiniz.



Resmî aile görseli

## Doğrulanmış teknik referanslar

| | |
|---|---|
| Model kodu | NR173 |
| Gövde grubu | N17 |
| Dişli yapısı | Helisel |
| Kademe | 3 |
| Giriş bağlantısı | Direkt motor akupleli; motor seçimi gerekli |
| Çıkış / montaj | Flanş bağlantılı, dolu mil |
| Standart çıkış mili çap/boy (mm) | Ø25/50 |
| Gövde grubu nominal torku (Nm, referans) | 200 |

Bir turda gerçekleşen hareketi ve dakikadaki hedef çevrim sayısını belirtin.

**Üretim adedi doğrudan redüktör devri midir?**

Her zaman değil. Mekanizmanın bir turdaki hareketi ve varsa ara aktarım oranı hesaba katılır.

## NR173 teklifini proses hızınıza göre şekillendirelim.

Temel model: tahvil, motor/giriş bağlantısı ve montaj pozisyonu teyit edilir. Gövde torku referanstır; seçili takımın çıkış değeri değildir. Görsel aileye aittir; boyut ve motor değişebilir.

# Yılmaz Redüktör NR173 Flange-Mounted Helical Gearmotor

## BASE MODEL / NR173

NR173 is the three-stage flange-mounted helical drive in the N17 group. For a feed or dosing mechanism, production rate must first be translated into mechanical output speed. Process data such as travel per revolution and cycles per minute help define the ratio needed for a useful quotation.



Official family visual

## Verified technical references

| | |
|---|---|
| Model code | NR173 |
| Housing group | N17 |
| Gear type | Helical |
| Stages | 3 |
| Input connection | Directly motor-coupled; motor selection required |
| Output / mounting | Flange mounted, solid output shaft |
| Standard output shaft diameter/length (mm) | Ø25/50 |
| Housing-group nominal torque (Nm, reference) | 200 |

Provide motion per revolution and target cycles per minute.

**Is production rate equal to gearbox speed?**

Not necessarily. Motion per revolution and any intermediate transmission ratio must be considered.

## Shape your NR173 quotation around the process speed.

Base model: ratio, motor/input interface and mounting position require confirmation. Housing torque is a reference, not a configured output rating. Family image; exact size and motor may differ.