

Yılmaz Redüktör NR272 Flanşlı Helisel Redüktör

TEMEL MODEL / NR272

NR272, N27 gövde grubunda iki kademeli flanşlı helisel tahrik sunar. 35 mm çaplı çıkış mili ve 70 mm mil boyu, flanş önündeki aktarım düzenini planlamak için kullanılabilir. Karıştırma gibi eksenel kuvvet doğurabilecek bir uygulamada standart N modeliyle özel karıştırıcı çıkışının aynı kabul edilmemesi, doğru ürün kapsamını belirlemek açısından önemlidir.



Resmî aile görseli

Doğrulanmış teknik referanslar

Model kodu	NR272
Gövde grubu	N27
Dişli yapısı	Helisel
Kademe	2
Giriş bağlantısı	Direkt motor akupleli; motor seçimi gerekli
Çıkış / montaj	Flanş bağlantılı, dolu mil
Standart çıkış mili çap/boy (mm)	Ø35/70
Gövde grubu nominal torku (Nm, referans)	450

Eksenel kuvveti ve karıştırıcı milinin bağımsız yataklanıp yataklanmadığını belirtin.

NR272 standart olarak özel karıştırıcı boğazlı mı?

Hayır. N serisinin özel karıştırıcı düzenleri ayrı kodlarla tanımlanır; uygulama için ayrıca seçilir.

NR272 teklifinde uygulamanızın yataklama ihtiyacını inceleyelim.

Temel model: tahvil, motor/giriş bağlantısı ve montaj pozisyonu teyit edilir. Gövde torku referanstır; seçili takımın çıkış değeri değildir. Görsel aileye aittir; boyut ve motor değişebilir.

Yılmaz Redüktör NR272 Flange-Mounted Helical Gearmotor

BASE MODEL / NR272

NR272 provides two-stage flange-mounted helical gearing in the N27 group. Its 35 × 70 mm output shaft supports layout planning. For mixing duties that create axial force, distinguish a standard N model from a dedicated agitator-output arrangement before deciding the supply scope.



Official family visual

Verified technical references

Model code	NR272
Housing group	N27
Gear type	Helical
Stages	2
Input connection	Directly motor-coupled; motor selection required
Output / mounting	Flange mounted, solid output shaft
Standard output shaft diameter/length (mm)	Ø35/70
Housing-group nominal torque (Nm, reference)	450

State axial loading and whether the mixer shaft has independent bearings.

Does NR272 include a special agitator output as standard?

No. Dedicated agitator arrangements have separate designations and require application-specific selection.

Review the bearing arrangement in your NR272 enquiry.

Base model: ratio, motor/input interface and mounting position require confirmation. Housing torque is a reference, not a configured output rating. Family image; exact size and motor may differ.