INOVANCE / IT7000

# IT7100E-INT

INOVANCE IT7100E-INT 10,1 inç HMI

Reçete değerleriyle proses durumunu aynı ekranda göstermek isteyen projeler için IT7100E-INT incelenebilir. 1024 × 600 çözünürlük, arayüz yerleşimi için 7 inç modelden farklı bir çalışma alanı sunar. Üreticinin seri föyü ekranı 10,1 inç olarak belirtir; güncel model kaydındaki 10 inç ifadesi sınıf tanımı olarak değerlendirilmiş ve fark kaynak notunda korunmuştur.




Üreticinin model kaydına atadığı ürün/gövde görseli. Ayrı tam kod etiketi doğrulanmadı; bazı modellerde ortak kullanılır.

## TEKNİK SEÇİM VERİLERİ

| | |
|---|---|
| Ekran sınıfı | 10.1 in |
| Çözünürlük | 1024 × 600 px |
| Besleme | 24 V DC ±20% |
| Anma giriş akımı | 300 mA |
| İşlemci | Cortex A8 1 GHz |
| Ethernet | 1 × RJ45 10/100 Mbit/s |
| Seri portlar | RS422/RS485; RS232; RS485 |
| Bellek (DRAM / Flash) | 256 MB / 256 MB |
| Ön / arka koruma | IP65 / IP20 |
| USB bağlantıları | 1 × USB-A; 1 × Mini USB |

Seri V0.3 föyü temel donanım için karşılaştırıldı; INT sipariş kodu güncel ürün kaydındandır. Panel kesimi için tam model çizimini teyit edin.

## UYGULAMA İÇİN SEÇİM

Pano kesitini eski bir broşür ölçüsünden hazırlamayın; tam INT kodunun montaj çizimini teyit edin. Reçete saklama ve PLC veri akışı uygulama tasarımına bağlıdır.

### Eski panel deliğine doğrudan takılabilir mi?

Bunu ekran boyutu belirlemez. Kesim ölçüsü, conta yüzeyi, montaj kelepçeleri ve bağlantı boşluğu tam model çizimiyle karşılaştırılmalıdır.

**TEKLİF TALEBİ**

Reçete alanlarını ve pano yerleşiminizi iletin; IT7100E-INT için donanım ve arayüz geliştirme teklifini hazırlayalım.

Resmî model kaydı · Üretici föyü

Automation teknik özetidir. Fiyat, stok, termin ve teknik revizyon teklif aşamasında teyit edilir.

INOVANCE / IT7000

# IT7100E-INT

INOVANCE IT7100E-INT 10.1 inch HMI

IT7100E-INT can be assessed when recipe values and process status need to share an operator screen. Its 1024 × 600 resolution provides a different layout area from the 7-inch model. The series brochure specifies 10.1 inches, while the current record says 10 inches; that naming difference is retained in the source notes.




Manufacturer-assigned product/enclosure visual. A separate full-code nameplate is unverified; some models share the image.

## TECHNICAL SELECTION DATA

| | |
|---|---|
| Display class | 10.1 in |
| Resolution | 1024 × 600 px |
| Supply | 24 V DC ±20% |
| Rated input current | 300 mA |
| Processor | Cortex A8 1 GHz |
| Ethernet | 1 × RJ45 10/100 Mbit/s |
| Serial ports | RS422/RS485; RS232; RS485 |
| Memory (DRAM / Flash) | 256 MB / 256 MB |
| Front / rear protection | IP65 / IP20 |
| USB connections | 1 × USB-A; 1 × Mini USB |

The V0.3 series flyer supports hardware comparison; the INT order code comes from the current product record. Confirm the exact mounting drawing before cutting.

## APPLICATION SELECTION

Do not cut the panel from an old brochure dimension. Confirm the exact INT mounting drawing, then design recipe storage and PLC data exchange for the application.

### Will it fit directly into an existing panel opening?

Screen size cannot establish that. Compare cutout, sealing surface, clamps and connection clearance with the exact-model mounting drawing.

### QUOTATION REQUEST

Provide recipe fields and the enclosure layout for a combined IT7100E-INT hardware and interface-development quotation.

Official model record · Manufacturer brochure

Automation technical summary. Confirm price, stock, lead time and technical revision in the quotation.