INOVANCE / SV670

SV670NS027I-INT

INOVANCE SV670NS027I-INT 27 A EtherCAT Servo Sürücü

27 A EtherCAT modeli, üç faz 200–240 V sınıfında yüksek akım gereksinimi olan eksenleri hedefleyen bir seçim adayıdır. FS eki olmadığından güvenli tork kesme donanımı bu koda dahil sayılmaz.



Üreticinin model kaydına atadığı ürün/gövde görseli. Ayrı tam kod etiketi doğrulanmadı; bazı modellerde ortak kullanılır.

TEKNİK SEÇİM VERİLERİ

Besleme sınıfı	3 faz 200-240 V AC
Sürekli çıkış akımı	27 A
Tepe çıkış akımı	67.5 A
Komut arayüzü	EtherCAT
STO	FS yok: dahil değil
Dijital kanallar	5 DI / 2 DO
Analog kanallar	2 AI / 1 AO
PC arayüzü	USB-C
Gövde	E
Kütle	3.60 kg

A01 kod ve seçim tablosu esas alınır. Şebeke fazı, FS seçeneği ve motor eşleşmesi tam kodla doğrulanır; tepe akım sürekli çalışma değeri değildir.

UYGULAMA İÇİN SEÇİM

67,5 A tepe akımın görev süresini sürücü kılavuzuyla eşleştirin.

Bu sürücü 400 V şebekeye bağlanır mı?

S sınıfı 200–240 V içindir; 380–480 V şebekeye doğrudan uygun kabul edilmez.

TEKLİF TALEBİ

Yük-zaman grafiğini paylaşın; yüksek akımlı S sürümünü değerlendirelim.

Resmî model kaydı · Üretici föyü

Automation teknik özetidir. Fiyat, stok, termin ve teknik revizyon teklif aşamasında teyit edilir.

INOVANCE / SV670

SV670NS027I-INT

INOVANCE SV670NS027I-INT 27 A EtherCAT Servo Drive

For high-current axes at three-phase 200–240 V, this 27 A EtherCAT model is a selection candidate. The code lacks FS, so torque-off hardware is not counted as included.



Manufacturer-assigned product/enclosure visual. A separate full-code nameplate is unverified; some models share the image.

TECHNICAL SELECTION DATA

Supply class	3 phase 200-240 V AC
Continuous output current	27 A
Peak output current	67.5 A
Command interface	EtherCAT
STO	No FS: not fitted
Digital channels	5 DI / 2 DO
Analogue channels	2 AI / 1 AO
PC interface	USB-C
Frame	E
Mass	3.60 kg

A01 ordering and selection charts are used. Verify supply phase, FS option and motor pairing by full code; peak current is not a continuous rating.

APPLICATION SELECTION

Check the allowable duty of the 67.5 A peak in the drive manual.

Can this drive connect to a 400 V supply?

The S class is for 200–240 V and must not be assumed suitable for direct 380–480 V input.

QUOTATION REQUEST

Share the load-time diagram to assess the high-current S variant.

Official model record · Manufacturer brochure

Automation technical summary. Confirm price, stock, lead time and technical revision in the quotation.