INOVANCE / SV670

SV670NT3R5I-INT

INOVANCE SV670NT3R5I-INT 3,5 A EtherCAT Servo Sürücü

INOVANCE SV670NT3R5I-INT, EtherCAT üzerinden komut alan 380-480 V sınıfında bir servo sürücüdür. 3,5 A anma akımı, etiketleme besleme ekseni gibi kontrollü hareket projelerinde motor eşleştirmesinin başlangıcıdır. Bu kodda FS eki bulunmaz; STO işlevi varmış gibi bir güvenlik tasarımı yapılmamalıdır.



Üreticinin model kaydına atadığı ürün/gövde görseli. Ayrı tam kod etiketi doğrulanmadı; bazı modellerde ortak kullanılır.

TEKNİK SEÇİM VERİLERİ

Şebeke sınıfı	3 faz 380-480 V AC
Anma çıkış akımı	3.5 A
Tepe çıkış akımı	11 A
Komut arayüzü	EtherCAT
STO seçeneği	FS eki yok: dahil değil
Dijital giriş / çıkış	5 DI / 2 DO
Analog giriş / çıkış	2 AI / 1 AO
PC bağlantısı	USB-C
Gövde sınıfı	C
Gövde kütlesi	1.30 kg

Akım ve seçenekler A01 kod/seçim tablosundandır. Motor gücü tek değere indirgenmez; tam motor eşleşmesi gerekir. Tepe akımın süresi kılavuzdan doğrulanır.

UYGULAMA İÇİN SEÇİM

Etiket ilerletme mesafesi, çevrim süresi ve yük ataletiyle motoru eşleştirin. EtherCAT ana kontrolör uyumu ve gerekli güvenli duruş donanımı ayrıca belirlenmelidir.

Bu kod EtherCAT ve STO özelliklerini birlikte içerir mi?

N harfi EtherCAT tipini tanımlar. STO seçeneği FS ekiyle ayrılır; bu sipariş kodunda FS yoktur.

TEKLİF TALEBİ

Etiketleme ekseninin hız profilini ve motor kodunu iletin; sürücü, kablo ve kontrolör uyumunu birlikte tekliflendirelim.

Resmî model kaydı · Üretici föyü

Automation teknik özetidir. Fiyat, stok, termin ve teknik revizyon teklif aşamasında teyit edilir.

INOVANCE / SV670

SV670NT3R5I-INT

INOVANCE SV670NT3R5I-INT 3.5 A EtherCAT Servo Drive

INOVANCE SV670NT3R5I-INT is a 380-480 V class servo drive commanded over EtherCAT. Its 3.5 A rated current is a starting point for matching a motor to a controlled-motion task such as label feeding. This code has no FS suffix, so the machine safety design must not assume an integrated STO option.



Manufacturer-assigned product/enclosure visual. A separate full-code nameplate is unverified; some models share the image.

TECHNICAL SELECTION DATA

Supply class	3-phase 380-480 VAC
Rated output current	3.5 A
Peak output current	11 A
Command interface	EtherCAT
STO option	No FS suffix: not fitted
Digital inputs / outputs	5 DI / 2 DO
Analogue inputs / outputs	2 AI / 1 AO
PC connection	USB-C
Frame class	C
Drive mass	1.30 kg

Current and options follow the A01 ordering/selection chart. No single motor power is assumed; verify the complete motor pairing and peak-current duration.

APPLICATION SELECTION

Match the motor using feed distance, cycle time and load inertia. Verify the EtherCAT master and separately specify the required safe stopping hardware.

Does this code include both EtherCAT and STO?

N identifies the EtherCAT type. STO is differentiated by the FS suffix, which is absent from this ordering code.

QUOTATION REQUEST

Send the label-feed motion profile and motor code for a drive, cable and controller compatibility quotation.

Official model record · Manufacturer brochure

Automation technical summary. Confirm price, stock, lead time and technical revision in the quotation.