INOVANCE / SV670

SV670PT012I-FS-INT

INOVANCE SV670PT012I-FS-INT 12 A Darbe/CAN STO Servo Sürücü

CANopen eksen mimarisini kullanan bir makinede SV670PT012I-FS-INT, EtherCAT sürücü seçmeden ilerlemek isteyen projeler için değerlendirilebilir. P tipi arayüz, 12 A anma akımı ve FS/STO seçeneği bu modelin temel ayrımlarıdır. Kontrolörün desteklediği hareket profili ve ağ çevrimi, uygunluğun ayrıca doğrulanması gereken parçalarıdır.



Üreticinin model kaydına atadığı ürün/gövde görseli. Ayrı tam kod etiketi doğrulanmadı; bazı modellerde ortak kullanılır.

TEKNİK SEÇİM VERİLERİ

Şebeke sınıfı	3 faz 380-480 V AC
Anma çıkış akımı	12 A
Tepe çıkış akımı	30 A
Komut arayüzü	Darbe / CANopen / CANlink
STO seçeneği	FS: var
Dijital giriş / çıkış	8 DI / 5 DO
Analog giriş / çıkış	2 AI / 1 AO
PC bağlantısı	USB-C
Gövde sınıfı	D
Gövde kütlesi	1.80 kg

Akım ve seçenekler A01 kod/seçim tablosundandır. Motor gücü tek değere indirgenmez; tam motor eşleşmesi gerekir. Tepe akımın süresi kılavuzdan doğrulanır.

UYGULAMA İÇİN SEÇİM

CANopen desteğini her kontrolörle hazır eksen uyumluluğu olarak yorumlamayın. Ağ cihaz profili, hız, düğüm sayısı ve yazılım sürümleri kontrol edilmelidir.

P tipi model EtherCAT ağına doğrudan bağlanır mı?

P ve N arayüzleri farklıdır. Bu P modeli için darbe/CAN seçenekleri değerlendirilir; EtherCAT gerekiyorsa uygun N kodu seçilmelidir.

TEKLİF TALEBİ

CANopen kontrolörünüzü ve ağ düzenini paylaşın; mevcut mimariye göre servo tedarik kapsamı hazırlayalım.

Resmî model kaydı · Üretici föyü

Automation teknik özetidir. Fiyat, stok, termin ve teknik revizyon teklif aşamasında teyit edilir.

INOVANCE / SV670

SV670PT012I-FS-INT

INOVANCE SV670PT012I-FS-INT 12 A Pulse/CAN STO Servo Drive

SV670PT012I-FS-INT can be considered for a machine that already uses a CANopen axis architecture. The P-type interface, 12 A rated current and FS/STO option distinguish this model. Controller motion-profile support and network timing remain separate compatibility checks before the unit can be selected for an existing system.



Manufacturer-assigned product/enclosure visual. A separate full-code nameplate is unverified; some models share the image.

TECHNICAL SELECTION DATA

Supply class	3-phase 380-480 VAC
Rated output current	12 A
Peak output current	30 A
Command interface	Pulse / CANopen / CANlink
STO option	FS: fitted
Digital inputs / outputs	8 DI / 5 DO
Analogue inputs / outputs	2 AI / 1 AO
PC connection	USB-C
Frame class	D
Drive mass	1.80 kg

Current and options follow the A01 ordering/selection chart. No single motor power is assumed; verify the complete motor pairing and peak-current duration.

APPLICATION SELECTION

Do not equate CANopen support with ready-made axis compatibility. Check device profiles, bit rate, node count and software versions.

Can this P-type model connect directly to EtherCAT?

P and N are different interface variants. Assess pulse/CAN commands for this P model and select a suitable N code when EtherCAT is required.

QUOTATION REQUEST

Share the CANopen controller and network arrangement for a servo-supply scope aligned with the existing architecture.

Official model record · Manufacturer brochure

Automation technical summary. Confirm price, stock, lead time and technical revision in the quotation.